

PERMAFAB es un tejido de poliéster con uniones cosidas en un 100 % que ofrece una combinación inusual de propiedades de gran resistencia y buena elongación para una excelente resistencia contra el estrés térmico. El tejido de poliéster **PERMAFAB** no se pudre con el transcurso del tiempo y es resistente a la humedad. **PERMAFAB** está diseñado para usarlo junto con los revestimientos **ALPHAGUARD**, **SOLARGARD 6083** y **SOLARGARD 2083** como recubrimiento para mantenimiento de superficies lisas y techos monocapa. **PERMAFAB** también se usa junto con el sellador acrílico **SOLARGARD Acrylic Sealer** para reparar tapajuntas, uniones, penetración y otras reparaciones de detalles.

INSTRUCCIONES

Preparación de la Superficie: La superficie debe estar limpia y bien preparada de acuerdo con las instrucciones del producto de inserción.

Aplicación: Corte el tejido **PERMAFAB** al tamaño adecuado. Aplique adhesivo o masilla específicos para techos de forma que cubra por completo. Coloque el **PERMAFAB** sobre el material recién aplicado y presione con una llana seca para asegurar la adhesión completa. Si está indicado, aplique capas adicionales de **PERMAFAB** y masilla o adhesivo. Aplique una capa final de masilla en toda el área para cubrir el **PERMAFAB**. Cuando repare ampollas que hayan sido cortadas, o cuando selle hendiduras que se extienden a través de la membrana del techo, utilice dos capas de **PERMAFAB** insertadas entre aplicaciones de masillas Tremco.

Limitaciones: La temperatura de aplicación debe ser mayor a 40°F (4.4°C). No lo aplique si va a llover. No se debe integrar ni aplicar directamente sobre ningún revestimiento **ALUMINATION**.

346545 TREMCO PERMAFAB



0 20066 44 164 7

TRUSTED ROOFING SOLUTIONS SINCE 1928

TREMCO



Permafab™
REINFORCEMENT FABRIC

6" x 300'

100% STITCHBONDED
POLYESTER FABRIC

STRENGTHENS
SEAMS, CRACKS,
JOINTS, TEARS
AND MORE

EXCEPTIONAL
FLEXIBILITY
AND STRENGTH

RESISTANT TO
ROT AND DECAY



346545
PERMAFAB

PERMAFAB is 100% stitchbonded, polyester fabric that offers an unusual combination of high strength properties with good elongation for excellent resistance against thermal stress. **PERMAFAB** polyester fabric will not rot as it ages and it is resistant to moisture. **PERMAFAB** is designed to be used in conjunction with **ALPHAGUARD**, **SOLARGARD 6083**, and **SOLARGARD 2083** coatings as a maintenance overlayment for smooth surfaces, and single-ply roofs. **PERMAFAB** is also used in conjunction with **SOLARGARD Acrylic Sealer** for flashing, seam, penetration, and other detail repairs.

DIRECTIONS

Surface Preparation: Surface must be clean and properly prepped per instructions on mastic or adhesive.

Application: Cut **PERMAFAB** to appropriate size. Apply a full coverage of the specified roofing mastic or adhesive. Set **PERMAFAB** into the freshly applied material and apply pressure with a brush or trowel to assure complete adhesion. If specified, apply additional courses of **PERMAFAB** and mastic/adhesive. Apply a top course of mastic in a full coverage to completely cover the **PERMAFAB**. When repairing blisters which have been cut open, or when sealing splits which extend through built-up roof membrane, use two piles of **PERMAFAB** embedded between applications of Tremco mastics.

Limitations: Application temperature shall be above 40°F (4.4°C). Do not apply when rain is imminent. Not to be directly embedded into or coated with any **ALUMINATION** coatings.

Limited Product Warranty: Should this product fail due to a defect, unless expressly agreed otherwise by Tremco in writing, purchaser's sole and exclusive remedy is that Tremco Incorporated will, at its option, either refund to the purchaser the amount paid for the product, or furnish at its expense sufficient product to restore a protective condition to the affected areas. Proof of purchase must be provided. At its discretion, Tremco may require inspection of the affected areas by a Tremco representative. Contact Tremco Product Support at 1-800-852-6013. Refer to product number and batch code. Please visit www.tremcoroofing.com for further information regarding additional warranties that may be available for your roofing system. **NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TREMCO, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING BUT NOT LIMITED TO MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

TREMCO

ROOFING & BUILDING MAINTENANCE
3735 Green Road, Beachwood, Ohio 44122
1-800-852-6013 | www.tremcoroofing.com

©2019 Tremco Roofing and Building Maintenance. All Rights Reserved.

25862 0219



03/06/19	SB	Roofing	
346545_ROF_0009_25862_0219_Tremco_6in_Permafab			
Principal Display Panel: 12"		Signal Word: n/a	Statement of Hazard: n/a
Other Cautionary Material: n/a		Other Cautionary Material (Back label): .0681"	
Other Cautionary Material (Address): .0641"		Net Wt: n/a	

All dimensions are based on the measurements within the label at 100% actual size.