



Dependable. Reliable. Professional.

# DRYER VENT INSTALLATION TAPE

**UL LISTED TAPE**



- Backing:** Printed Biaxially-Oriented Polypropylene Film
- Adhesive:** Acrylic
- Liner:** N/A
- Specifications:** UL 181B-FX Listed
- Colors:** Metallic
- Available Size:** 1.89 in x 30 yd (48 mm x 27.4 m)

## Applications

- Designed and sized for sealing dryer vent exhaust ducts and connections to increase system performance
- Tough, contractor-grade closure system intended for use on UL Listed flexible, non-metallic ducts

## Features

## Benefits

UL 181B-FX Listed	<ul style="list-style-type: none"> <li>• Meets code requirements for sealing flexible air ducts and connections</li> <li>• Can contribute toward satisfying EA Credit 1 (Optimize Energy Performance) under LEED®</li> </ul>
Acrylic Adhesive	<ul style="list-style-type: none"> <li>• Excellent, long-lasting adhesion</li> <li>• Low-odor adhesive</li> <li>• Mold and moisture-resistant</li> </ul>
Biaxially-Oriented Polypropylene Film	<ul style="list-style-type: none"> <li>• Tough and durable</li> <li>• Hand tearable for simple, quick installation</li> <li>• 181B-FX printed for easy inspector identification</li> </ul>
Low VOC Content	<ul style="list-style-type: none"> <li>• Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

## Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	3.1 mils	79 µm	ASTM D-1000
<b>Adhesion to Steel</b>	45 oz/in	4.92 N/cm	PSTC-101
<b>Tensile Strength</b>	34 lb/in	59.54 N/cm	ASTM D-1000
<b>Installation Temperature</b>	-10 to 180 °F	-17 to 82 °C	
<b>Operating Temperature</b>	-40 to 212 °F	-40 to 100 °C	
<b>VOC Content</b>	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 24 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Parkway Franklin, MA 02038  
 1-800-343-7875 Fax 1-800-328-4822  
[www.nashuatape.com](http://www.nashuatape.com)