



MODEL DD50PE

DEHUMIDIFIER



WORRY-FREE PUMP FUNCTION
 THE PATENTED PUMP FUNCTION ALLOWS THE UNIT TO CONTINUOUSLY DISCHARGE MOISTURE WITHOUT CONSTANTLY EMPTYING A BUCKET. THE UNIT CAN PUMP WATER UPWARD TO DRAIN OUT A BASEMENT WINDOW OR INTO A SINK, UP TO 16' WITH THE PROVIDED HOSE.



LCD ELECTRONIC CONTROLS
 CHOOSE THE IDEAL HUMIDITY LEVEL BY ADJUSTING THE HUMIDISTAT. THE ELECTRONIC CONTROLS ALLOW YOU TO MONITOR RELATIVE HUMIDITY AND TEMPERATURE.



VISIBLE WATER LEVEL
 WITH ITS FRONTALLY LOCATED TANK AND TRANSPARENT WATER LEVEL WINDOW, YOU CAN EASILY SEE HOW MUCH WATER HAS BEEN COLLECTED.



MODEL	DD50PE
SAP CODE	0148850208
UPC	0-44387-05050-0
SCC14	NA
UNIT (LxWxH)	15.3 x 12.4 x 24.3
VOL Unit ft3	2.7
UNIT Weight (Lbs)	37.9
CARTON (LxWxH)	14 x 16.5 x 27.2
VOL Carton ft3	3.6
CARTON Weight	41.9
Pcs per Master	1
MASTER (LxWxH)	
VOL Master ft3	
MASTER Weight	
CONTAINER 20'	270
CONTAINER 40'	549
CONTAINER 40HC'	
CONTAINER 45'	

EMPTY THE COLLECTED WATER 3 WAYS:

- CONTINUOUSLY THROUGH **PATENTED PUMP SYSTEM:** [16 FT HOSE INCLUDED]
- PASSIVELY THROUGH THE 3' HOSE [INCLUDED]
- DIRECTLY INTO THE TANK [6.0 LITTER CAPACITY]

ELECTRONIC CLIMATE CONTROL WITH LCD DISPLAY:

- ADJUSTABLE HUMIDISTAT
- ROOM THERMOSTAT
- 24-H TIMER
- ANTI-FROST DEVICE (DOWN TO 41 °F)
- FAN SPEED CONTROL — 2 FAN SPEEDS

TANK CONTROL SYSTEM WITH ALARM

CAN BE EASILY MOVED BY CASTOR WHEELS & HANDLES

POWER: 1500W



R410A REFRIGERANT GAS

UPDATED 4/05/2013

DISCLAIMER: FEATURES AND COLORS ARE TENTATIVE AND SUBJECT TO CHANGE WITHOUT NOTICE.