

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 12-Jun-2013

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Alkaline Battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Alkaline battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Spectrum Brands, Inc
Supplier Address 3001 Deming Way
Middleton WI 53562
USA
Supplier Phone Number Phone:703-527-3887
Contact Phone1-479-254-1729
Supplier Email marcy.stokes@spectrumbrands.com
Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.


| | |
|---|---------------------------|
| Acute toxicity - Oral | Category 4 |
| Acute toxicity - Inhalation (Gases) | Category 4 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 1 Sub-category A |
| Serious eye damage/eye irritation | Category 1 |



Specific target organ toxicity (repeated exposure)

Category 2

GHS Label elements, including precautionary statements**Emergency Overview**

| | | | |
|---|---------------|-----------------------|----------------------|
| Signal word | Danger | | |
| Hazard Statements | | | |
| Harmful if swallowed | | | |
| Harmful if inhaled | | | |
| Causes severe skin burns and eye damage | | | |
| May cause damage to organs through prolonged or repeated exposure | | | |
|  | | | |
| <p>This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.</p> | | | |
| Appearance | Solid | Physical State | Solid |
| | | | Odor Odorless |

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician
 Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician if you feel unwell
 Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

5% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---------------------|-----------|----------|--------------|
| Manganese dioxide | 1313-13-9 | 15 - 40 | * |
| Steel | 7439-89-6 | 19-23 | * |
| Zinc | 7440-66-6 | 10 - 30 | * |
| Potassium hydroxide | 1310-58-3 | 5 - 10 | * |
| Graphite | 7782-42-5 | 3 - 7 | * |
| Barium sulfate | 7727-43-7 | 3 - 7 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES**First aid measures****General Advice**

First aid is upon rupture of sealed battery.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice.

Inhalation

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.

- Ingestion** Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
- Self-protection of the first aider** Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Uniform Fire Code

Corrosive: Other--Solid
Toxic: Solid
Oxidizer: Class 1--Solid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe dust. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------|-----------|----------|------------|
|---------------|-----------|----------|------------|



| | | | |
|----------------------------------|--|--|--|
| Manganese dioxide 1313-13-9 | TWA: 0.02 mg/m ³ Mn TWA: 0.1 mg/m ³ Mn | (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn | IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ Mn |
| Zinc 7440-66-6 | STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction | TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction | IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume |
| Potassium hydroxide 1310-58-3 | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| Graphite 7782-42-5 | TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers | TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural | IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust |
| Barium sulfate 7727-43-7 | TWA: 5 mg/m ³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Face protection shield.

Skin and Body Protection

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. Do not breathe dust.

9. PHYSICAL AND CHEMICAL PROPERTIES



Physical and Chemical Properties

| | | | |
|-----------------------|--------------------------|-----------------------|--------------------------|
| Physical State | Solid | Odor | Odorless |
| Appearance | Solid | Odor Threshold | No information available |
| Color | No information available | | |

| <u>Property</u> | <u>Values</u> | <u>Remarks</u> | <u>Method</u> |
|---|----------------------|-----------------------|----------------------|
| pH | No data available | None known | |
| Melting / freezing point | No data available | None known | |
| Boiling point / boiling range | No data available | None known | |
| Flash Point | No data available | None known | |
| Evaporation Rate | No data available | None known | |
| Flammability (solid, gas) | No data available | None known | |
| Flammability Limit in Air | | | |
| Upper flammability limit | No data available | | |
| Lower flammability limit | No data available | | |
| Vapor pressure | No data available | None known | |
| Vapor density | No data available | None known | |
| Specific Gravity | No data available | None known | |
| Water Solubility | Immiscible in water | None known | |
| Solubility in other solvents | No data available | None known | |
| Partition coefficient: n-octanol/water | No data available | None known | |
| Autoignition temperature | No data available | None known | |
| Decomposition temperature | No data available | None known | |
| Kinematic viscosity | No data available | None known | |
| Dynamic viscosity | No data available | None known | |
| Explosive properties | No data available | | |
| Oxidizing Properties | No data available | | |

Other Information

| | |
|-----------------------------------|-------------------|
| Softening Point | No data available |
| VOC Content (%) | No data available |
| Particle Size | No data available |
| Particle Size Distribution | |

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.

Inhalation

Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation.

Eye Contact

Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.

Skin Contact

Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.

Ingestion

Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|-----------------------|-------------|-----------------|
| Manganese dioxide 1313-13-9 | = 9000 mg/kg (Rat) | - | - |
| Potassium hydroxide 1310-58-3 | = 214 mg/kg (Rat) | - | - |
| Graphite 7782-42-5 | > 10000 mg/kg (Rat) | - | - |

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Cardiovascular system. Liver.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

785.00 mg/kg

ATEmix (inhalation-gas)

10,465.00 ppm (4 hr)

ATEmix (inhalation-dust/mist)

3.50 mg/l

ATEmix (inhalation-vapor)

26.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

| Chemical Name | Toxicity to Algae | Toxicity to Fish | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|----------------------------------|---|---|----------------------------|------------------------------|
| Zinc 7440-66-6 | 96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata) | 96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss) | | 48h EC50: 0.139 - 0.908 mg/L |
| Potassium hydroxide 1310-58-3 | | 96h LC50: = 80 mg/L (Gambusia affinis) | | |

Persistence and Degradability

No information available.

Bioaccumulation

| Chemical Name | Log Pow |
|----------------------------------|---------|
| Manganese dioxide 1313-13-9 | <0 |
| Potassium hydroxide 1310-58-3 | 0.83 |

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 181

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste |
|----------------------------------|----------------------------|
| Zinc 7440-66-6 | Ignitable powder Toxic |
| Potassium hydroxide 1310-58-3 | Toxic Corrosive |
| Barium sulfate 7727-43-7 | Toxic soluble |

14. TRANSPORT INFORMATION

DOT NOT REGULATED

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory



DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|-------------------------------|-----------|----------|-------------------------------|
| Manganese dioxide - 1313-13-9 | 1313-13-9 | 15 - 40 | 1.0 |
| Zinc - 7440-66-6 | 7440-66-6 | 10 - 30 | 1.0 |
| Barium sulfate - 7727-43-7 | 7727-43-7 | 3 - 7 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|----|
| Acute Health Hazard | No |
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Zinc 7440-66-6 | | X | X | |
| Potassium hydroxide 1310-58-3 | 1000 lb | | | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|----------------------------------|--------------------------|------------------------------------|---|
| Zinc 7440-66-6 | 1000 lb | | RQ 454 kg final RQ RQ 1000 lb final RQ |
| Potassium hydroxide 1310-58-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|----------------------------------|------------|---------------|--------------|--------------|----------|
| Manganese dioxide 1313-13-9 | | | X | X | X |
| Zinc 7440-66-6 | X | X | X | X | |
| Potassium hydroxide 1310-58-3 | X | X | X | X | |
| Barium sulfate 7727-43-7 | X | X | X | X | |
| Graphite 7782-42-5 | X | X | X | | |



International Regulations**Mexico****National occupational exposure limits**

| Component | Carcinogen Status | Exposure Limits |
|--|-------------------|------------------------------------|
| Manganese dioxide 1313-13-9 (15 - 40) | | Mexico: TWA= 0.2 mg/m ³ |
| Graphite 7782-42-5 (3 - 7) | | Mexico: TWA= 2 mg/m ³ |

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

Non-controlled

| |
|------------------------------|
| 16. OTHER INFORMATION |
|------------------------------|

| | | | | |
|-------------|-------------------------|-----------------------|--------------------------|--|
| NFPA | Health Hazards 0 | Flammability 0 | Instability 0 | Physical and Chemical Hazards - |
| HMIS | Health Hazards 0 | Flammability 0 | Physical Hazard 0 | Personal Protection X |

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 12-Jun-2013

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet