

Technical Data: PRO-555 Updated: 4/11/17



# **PRO-555**

# **Extreme Tack Wallcovering Adhesive**

**Wallcovering Adhesive** 

**Product Number(s):** 11905, 11901

Base: Modified starch and Synthetic polymer

#### **Product Information**

**General Properties:** PRO-555 Extreme Tack is a high tack, low moisture adhesive for applying vinyl wallcovering over surfaces where extreme adhesion is required.

- Maximum wet-tack
- High solids/low moisture
- Not strippable
- Recommended for application with a roller or brush
- Do not dilute
- LEED compliant

**Recommended Uses:** Applying vinyl wallcovering over surfaces where extreme adhesion is required.

<u>NOT</u> Recommended For: Pre-pasted wallpaper, delicate wallcoverings, or use in a pasting machine.

Compatible Coatings: All Roman primers

**Substrates:** Apply over new bare drywall, sound latex paint, and surfaces properly primed with a Roman wallcovering primer.

**Mildew-Resistant:** All Roman products contain biocides for in-can preservation

# **Specification Data**

Percent Solids: Approximately 59%

Coverage: Up to approx. 160 square feet per gallon

Viscosity: Approximately 17,000 cps

VOC (actual): Zero

as calculated per EPA Method 24

Storage: Avoid freezing; keep in cool, dry place.

**Drying Time:** Drying time will vary depending on the temperature, ventilation and humidity of the room.



Technical Data: PRO-555 Updated: 4/11/17

### Application Instructions

**Surface Preparation:** Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, damaged wallboard or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

**Dilution:** Do not dilute.

**Application Method:** Use only when the room temperature is above 50 °F. Apply a thin, even coat of adhesive with a 3/8-inch nap roller or brush. IMPORTANT: A thick coat is less effective than a thin coat.

**Clean-Up:** Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls. Residual adhesive can be difficult to remove after it dries.

## Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

# **Limited Warranty**

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

#### Caution

This product contains no substances which, at their given concentration, are considered to be hazardous to health. **KEEP OUT OF REACH OF CHILDREN**. Do not ingest. IF IN EYES OR ON SKIN, wash with plenty of water. Do not freeze. Keep container tightly closed. WARNING: This product contains a chemical known to the State of California to cause cancer and/or birth defects or other reproductive harm.