

SPECIFICATIONS VALENCIATM WALL MOUNT RANGE HOODS



500 CFM/11.0 SONES @ 0.10" WG., 120 Volts, 3.8 amps, 60 hz.

• **Dimensions**

Overall bottom projection - 193/4" Height (less chimney) -91/4" Available widths: 30" & 36"

Hood Body

All metal cold rolled or stainless steel, finished in powder coat or brushed stainless steel.

• Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz., 3.0 amps.

• Lighting

Two - GU10 base, MR16, 50 watt halogen lights.

• **Ducting Options**

Vertical ducting: 6" round duct adapter complete with back draft damper ensuring quiet operation. Ductless: Requires charcoal filter (not included).

Blower Wheel

Dual inlet, electronically balanced polymeric centrifugal blower wheel, 5^{1/4"} width 59 paddles.

• Mounting


Wall mounted. Install 24" to 36" from cooking surface.

• Filters

Grease Filter: Dishwasher safe, BCGF-01 (included). Charcoal Filter: BCCF-02 (not included).

<u>Available Finishes</u>

White, Black & Stainless Steel.



				EXPAN	IDED I	PERFO	RMANC	E				
	Static Pressure (inches of w.g.)								Sones @ .1 SP	Fan Speed RPM	Power Watts	
	0	0.1	0.12	5 0.25	0.375	5 0.5	0.75	1.0				
Air Flow - CFM	508	500	498	488	477	465	440	413	11.0	2500	450	
PROJECT						ARCHITE	CT					
LOCATION	ENGINEER											
CONTRACTOR						SUBMITTED BY				DATE		
FAN MODEL NUMBER NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY			EQUIPMENT MARKS		
	U.S.: 820 Lincoln Avenue								(Canada: 8 Edvac Drive		
(EI)			West Chester, Pennsylvania 1938							6 Brampton, Ontario L6S 5F		
US		Tel: (610) 692-7400 • 877-304-3785								Tel: (905) 456-2033		
Intertek	Fax: (610) 696-8048									Fax: (905) 456-1015		

Specifications subject to change without notice.