SDS SAFETY DATA SHEET

Prepared For	:	Xinxiang hongli Power Science and Technology Co., Ltd Dayang Village South, ZhaiPo Town, Xinxiang, China
Prepared By	:	Shenzhen LCS Compliance Testing Laboratory Ltd. 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

 Issue Date
 :
 2017.04.27

 Report Number
 :
 LCS170412016AS 001

Written by: _____ Approved by: _____





The supplier identified below generated this SDS using the LCS SDS template. LCS did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. LCS makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 LCS LLC. All rights reserved.

Section 1-Chemical Product and Company Identification

Product Name: Li-ion Cell

Other means of identification

Synonyms: None

Model: 18650

Rating of Battery: DC3.7V, 1200mAh, 4.44Wh

Weight:37g

Manufacture: Shenzhen KingBoard Technology Co., Ltd.

Address: Bldg. A, Dakanglong Industry Zone Dabuxiang, Guanlan China

Post Code: 453700 Fax No: 0373-5632168

Emergency Telephone: 0373-5632158

Section 2- Hazards Identification

(a) Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR

1910.1200). This product is an article which is a sealed battery and as such does not require an SDS per the

OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 2
Specific target organ toxicity (repeated	Category 1
exposure)	

(b) GHS Label elements, including precautionary statements

Emergency Overview


Signal word Dang

Danger

Hazard Statements

Causes skin irritation Causes serious eye damage Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure





15% of the mixture consists of ingredient(s) of unknown toxicity.

(e) Other information

No information available.

(f) Interactions with Other Chemicals

No information available.

Section 3- Composition/Information on Ingredient

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Chemical Name	Molecular formula	CAS No.	Weight (%)
Lithium cobalt oxide	LiCoO2	12190-79-3	40
Carbon Black	С	1333-86-4	30
Polypropylene	(C3H6)n	9003-07-0	10
Lithium hexafluorophosphate	F6LiP	21324-40-3	16.6
Nickel	Ni	7440-02-0	0.6
Aluminium	AI	7429-90-5	2.8

Section 4- First Aid Measures

The battery is not hazard with eye and skin contact under normal circumstance. In case of the enclosure is

damaged, the battery can not be used and touched. It is safety except that the battery is damaged by fire or

rupture. The leakage of internal hazardous substance and formation of hazardous substance would occur, take the

following measures if contact with the battery.

Skin touch: Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

Eyes touch: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Seek immediate medical attention/advice.

Inhalation: Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious

person.DoNOT induce vomiting. Call a physician.



Self-protection of the first aider: Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Information for doctor

Most important symptoms and effects, both acute and delayed: no further relevant information available.

Indication of any immediate medical attention and special treatment needed: No further relevant information

available

Section 5- Fire Fighting Measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO2 as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials. Hazardous combustion products: CO, CO2, Metal oxides, Irritating fumes.

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filter mask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

Section 6- Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed wit sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic

lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth,

canalization or waters.

Section 7- Handling and Storage

Precautions for safe handling

<u>Handling</u> In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

Conditions for safe storage, including any incompatibilities

<u>Storage</u> Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.Keep out of the reach of children.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases.

Section 8- Exposure Controls, Personal Protection

(a)Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (CoLiO2)	TWA: 0.02 mg/m ³	-	
Graphi te	TWA: 2 mg/m ³ respirable fraction all forms excep	dust synthetic	IDLH: 1250 mg/m ³
7782-42 -5	graphite fibers	TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mpocf	TWA: 2.5 mg/m ³ respirable dust
1-Propene, 1,1,2,3,3,3-hexafluoro-, polymer with 1,1-difluoroethene 9011-17 -0	TWA: 2.5 mg/m³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	
Phosphate(1-), hexafluoro-, lithium 21324-40 -3	TWA: 2.5 mg/m³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	

Safety Data Sheet

Carbon black	TWA: 3 mg/m ³ fraction	inhalable	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³	
1333-86	Indettori		(vacated) TWA: 3.5	TWA: 3.5	
-4			mg/m ³	mg/m^3	
ACGIH TLV: American Confere	nce of Governmental In	dustrial Hygiei	nists -Threshold I imit Valı	TWA: 0.1 mg/m ³ Carbon black	
Safety and Health Administratio					
Other Exposure Guidelines					
F.2d 962(11th Cir., 1992) Se	_	-			
(b) Appropriate engineerin					
Engineering Measures:		vash stations	3.Ventilation syste	ms	
(c) Individual protection m	-				
Respiratory protection: No				from the battery protect	
	-				
			gloves. If battery is burn	-	
im	mediately. In abuse, u	use NIOSH a	approved acid gas filter	mask or self-contained	
br	eathing apparatus.				
Hand protection: None und	er normal use. In cas	e of spilling,	use PVC, neoprene or	nitrile gloves of 15miles	
(0.015 in	(0.015 inch) or thicker.				
Eye/Face protection: None	required under norma	al conditions.	Use approved chemica	al work safety goggles or f	
ace shield, if handling a leaking or rupture battery.					
Skin and boby protection:	No necessary under i	normal use. l	Jse rubber apron and p	rotective working in case of	
handling of a rupture battery.					
Other protective equipmer	t: Chemical resistanc	e clothing is	recommended along w	ith eye wash station and	
	safety shower should be available. Work hygienic practices: Use good chemical				
hygiene practice. Wash hands after use and before drinking, eating or smoking.					
	Wash hands thoroughly after cleaning-up component spill caused by leaking				
	battery. No eating, drinking, or smoking in battery storage area. Launder				
contaminated cloth before reuse.					
Section 9- Physical and Chemical Properties					
Physical and Chemical Properties					
Physical state	Solid				
Appearance	No information availab	ole Odo	or	No information available	
Color	No information availab		or Threshold	No information available	



	Γ		
Property	Values	Remarks Method	
PH	None known	None known	
Melting / freezing point	None known	None known	
Boiling point / boiling range	None known	None known	
Flash Point	None known	None known	
Evaporation Rate	None known	None known	
Flammability (solid, gas)	None known	None known	
Flammability Limit in Air	Γ		
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	No data available	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperatur	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available	None known	
Oxidizing properties	No data available	None known	
Other Information			
Softening Point	No data available		
VOC Content (%)	No data available		
Particle Size	No data available		

Section 10- Stability and reactivity

Reactivity: No data available.

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous rections : None under normal processing.

Conditions to avoid: None known based on information supplied.

Incompatible materials: Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products: None known based on information supplied.

Section 11- Toxicological information

Information on likely routes of exposure

Product Information: Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:

Inhalation: Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact: Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on

components). Severely irritating to eyes. May cause irreversible damage to eyes.

Skin contact: Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Prolonged contact may cause redness and irritation.

Ingestion: Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical name	Oral	Dermal LD50	Inhalation LC50
Propylene carbonate 108-32-7	= 29000 mg/kg(Rat)	> 20 mL/kg (Rabbit)	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Information on toxicological effects

Symptoms: Erythema (skin redness). May cause redness and tearing of the eyes. May cause blindness. Burning.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: No information available.

Mutagenic Effects: No information available.

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGI	IAR	NT	OSH
Lithium Cobalt Oxide	A3	Group 2B		Х
(CoLiO2)				
12190-79-3				
Carbon black	A3	Group 2B		Х
1333-86-4				
Group 2B - Possibly	Agency for Research o Carcinogenic to Humans		artment of Labor)	
Reproductive toxicity:	No information availa	ble.		
STOT- single exposure	e: No information avai	lable.		



STOT-repeated exposure: Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity: Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. Carbon black has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects: Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Aspiration Hazard: No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 7,819.00 mg/kg ATEmix (dermal) 6,300.00 mg/kg (ATE)

Section 12- Ecological Information

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propylene carbonate 108-32-7	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: > 1000 mg/L (Cyprinus carpio) 96h LC50: = 5300 mg/L (Leuciscus idus)	EC50 > 10000 mg/L 17 h	48h EC50: > 500 mg/L
Carbon black 1333-86-4				24h EC50: > 5600 mg/L

Persistence and Degradability

No information available.

BioaccumLCSation

Chemical	Log
Propylene carbonate	0.48
108-32-7	

Other adverse effects

No information available.

Section 13- Disposal Considerations

Waste treatment methods

Disposal methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. ConsLult the appropriate state, regional, or local regulations for additional



requirements.

Contaminated Packaging: Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes: 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical	California Hazardous Waste
Lithium Cobalt Oxide (CoLiO2)	Toxic
12190-79-3	

Section 14 – Transport Information

Note:

The transportation of Lithium-ion Battery and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation

listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision188 of IMO-IMDG Code"

<u>DOT</u> :	NOT REGLCSATED		
Proper Shipping Name	NON-REGLCSATED		
Hazard Class	N/A		
Emergency Response Guide	Number 147		
TDG	Not regulated		
<u>MEX</u>	Not regulated		
<u>ICAO</u>	Not regulated		
IATA Proper Shipping Name: Hazard Class	Not regulated NONREGULATED N/A		
IMDG/IMO Hazard Class EmS-No.	Not regulated N/A F-A, S-I		
<u>RID</u>	Not regulated		
ADR	Not regulated		
ADN_	Not regulated		
Section 15- Regulatory information			

International Inventories

TSCA DSL

Complies All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold
Lithium Cobalt Oxide (CoLiO2) - 12190-79-3	12190-79-3	15 -	0.

SARA 311/312 Hazard Categories

Acute Health Hazard	NO
Chronic Health Hazard	NO
Fire Hazard	NO
Sudden release of pressure hazard	NO
Reactive Hazard	NO

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65		
Carbon black - 1333-86-4	Carcinogen		
U.S. State Dight to Know Degulations			

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (CoLiO2)	X		Х	Х	Х
Graphite 7782-42-5	Х	х	Х		
Ethylene carbonate 96-49-1		х	Х		
Dimethyl carbonate 616-38-6	х	х	Х		
Diethyl carbonate 105-58-8	Х	х	х		
Carbon black 1333-86-4	Х	х	Х		Х

INC	National occupational exposure limits				
	Component	Carcinogen Status	Exposure Limits		



Graphite 7782-42-5(10 - 30)				Mexico: TWA= 2 mg/m ³	
Carbon black 1333-86-4 (1 - 5)				Mexico: TWA 3.5 mg/m ³ Mexico: STEL 7 mg/m ³	
Mexico - Occupational Ex	posure Limits - Carcinogens	1			
Canada WHMIS Hazard Class Non-controlled					
Section 16- Other	r Information				
NFPA Health Hazards 1	Flammability 0	Instability 0	Physical and C	hemical Hazards -	
HMIS Health Hazards 0	Flammability 0	Instability 0	Physical Hazard 0	Personal Protection X	
at the date of its pupprocessing, storage,	blication. The informative transportation, dispos	ation given is desi sal and release ar	igned only as a guidar nd is not to be consid	edge, information and belief nce for safe handling, use, ered a warranty or quality	

specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



Photos Document

