

EXL2

LED Edge Lit Exit Sign

Product Description

The EXL2 LED Edge Lit Exit Series presents a contemporary design with ease of installation and dependability in mind. Constructed of impact-resistant, optically clear acrylic, choose from clear single-faced or mirrored double-faced panels. High output LEDs deliver an indirect, evenly illuminated edge-lit exit sign with exceptional light distribution and a maintenance-free nickel-cadmium battery for long life. The EXL2 Series offers flexible installation for surface ceiling, wall or end mount options along with field adjustable chevrons for universal configuration based on your application's directional needs.

- Construction**
- Specification grade aluminum extrusion design
 - Optically clear, impact resistant acrylic panels with lettering
 - Single or double faced configurations available

- Electrical**
- LED light engine provides consistently bright, even EXIT legend illumination with red or green LEDs
 - Maintenance-free NiCad battery provides 90-minute emergency operation
 - 120/277VAC Dual Voltage Operation, 60Hz input
 - Fully-illuminated 6" letter height with 3/4" stroke
 - Low voltage disconnect eliminates deep discharge
 - Brown-out, short circuit and voltage surge protection
 - LED Indicator Light & Self-Test Push Button Switch
 - Damp Location Rated 0°C - 40°C
 - UL Listed to Standard 924 (Emergency Lighting)
 - NFPA 101 (Life Safety Code) compliant
 - NFPA 70 (National Electrical Code) compliant

- Finish**
- Satin finished aluminum housing
 - Available with either clear (single faced) or mirrored backing (double face)
 - Available with either green or red lettering

- Installation**
- No special tools required
 - Mounting plate allows for surface ceiling, wall or end mount options
 - Field-installable, removable chevron directional indicators for all configurations
 - Chevron mounting template simplifies directional application
 - For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

- Warranty**
- 2-year limited system warranty standard
 - Warranty does not cover product failure due to an overvoltage event (power surge)

PRODUCT INFORMATION

Input Voltage:	120/277VAC
Power Draw:	2.3W

Ordering Information					
Example: EXL2-10UNV-AL-CL-G-1					
Series	Version	Voltage	Backing Material	Letter Color	Number of Sides
EXL2	10 (Version 1)	UNV (120-277V)	CL (Clear - single only)	G (Green)	1 (Single)
			MR (Mirrored - double only)	R (Red)	2 (Double)

Specifications and dimensions subject to change without notice

Project

Catalog

Type

Date

