



Buy it for looks. Buy it for life.®

FAUCET DESCRIPTION

- Metal construction with various finishes identified by suffix
- High arc spout provides the height and reach to fill or clean large pots
- 2 or 4 hole-mount
- Flexible supply lines with 3/8" compression fittings
- 360° rotating spout
- Includes hose and side spray
- Duralock™ Quick Connect Installation

OPERATION

- Single handle lever
- Temperature controlled by 100° arc of handle travel

FLOW

- Aerator is limited to 1.5 gpm max (5.7 L/min)

CARTRIDGE

- 1255™ Duralast™ cartridge
- Nonmetallic/nonferrous and stainless steel material

STANDARDS


- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein
- Certified to ANSI/NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA ♿ for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations

Specifications



Noell™ Single Handle High Arc Kitchen Faucet with Side Spray

Models: 87506 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 2 OR 4 HOLES: 1-1/2" (38MM) MIN. DIA. HOLES FOR VALVE AND DECK PLATE (IF INSTALLED) AND A 1-1/4" (32MM) MIN. DIA. HOLE FOR SIDE SPRAY

4 HOLES ON 4" CENTERS WHEN INSTALLED WITH DECK PLATE
2 HOLES ON 8" CENTERS WHEN INSTALLED WITHOUT PLATE

