

SANIBEST[®] Pro

Full bathroom for demanding situations



Conceal your pump behind the wall using our Extension Pipe (Page 8)

- Complete your installation using **Saniflo's rear discharge toilets**. (Please refer to page 7 for more information)
- **Mix and match** your fixtures (shower, bathtub and sink) from **different brands** to create your personalized one of a kind bathroom.
- Take advantage of the **different types of installations** Saniflo has to offer. From having the pump right behind the toilet to concealing the pump and pipes behind the wall. (Please refer to page 6 for more information)

EASY SERVICE ACCESS PANEL



Part# 013

Pump Type:
GRINDER

Discharge up to:
↑ 25 Ft. ↑ and/or ← 150 Ft. →

Power/Electrical Information:
115V - 60 Hz / 1 HP / 9.0 A

Dimensions:
H 10 1/2" (26.8cm) x W 20 3/8" (52cm) x D 8" (20.5cm)

Discharge pipe diameter:
3/4" rigid pipe

Discharge flow rate at 25':
19 gal per min (72 liters per min)

Discharge flow rate at 3':
38 gal per min (145 liters per min)

Max. Temperature:
104°F (40°C)

Possible Connections:



- 3/4" Discharge
- 1 1/2" Vent
- Connect to Saniflo toilet
- Connect to shower, bathtub, sink or washing machine**

** Indirect Connection



Choose any shower, bathtub or sink and enjoy your dream bathroom.