Application Information

Etched FX premium glass etch vinyl can be easily applied to any smooth glass surface. The translucent films have a stylish and unique pattern to give you privacy with style, while allowing natural light to enter the room.

• PROVIDES PRIVACY • HIDES UNWANTED VIEWS

• ACCENTS THE ROOM • APPLIES EASILY

• TRIM TO FIT OR ADD PANELS

- 1. Measure area of application to ensure proper fit. Some areas may require the purchase of several kits. If necessary, trim the etched film for a custom fit.
- 2. Thoroughly clean application area using alcohol or any Ammonia based window cleaner. Must be free of dirt and grease.
- 3. Tape your graphic into desired position, the graphic must be flat. Firmly tape center of graphic.
- 4. Un-tape one side of graphic and fold back over top of side taped to glass. Reveal corners and tape them down.
- 5. Carefully remove paper backing; Cut backing off at center.
- 6. Fold graphic back into position, pulling taut.
- 7. Squeegee starting from center rubbing in an up and down motion.
- 8. Remove remaining tape and repeat steps 4 thru 7.
- 8. Carefully remove clear application tape at 180 degree angle. If graphic is lifting, lay application tape back down and re-rub.
- 10. Cut door seams 1/8 inch back using razor blade if desired.
- 11. Any remaining air bubbles smaller than 1/8 inch will dissipate within one week.