TECHNICAL DATA

1	Flow pressure	
	-min.	15 PSI (1.0 bar)
	-recommended	75 PSI (5.0 bar)
	If greater than 5 bar, install pressure reducer.	
2	Operating pressure	
	-max.	150 PSI (10.0 bar)
3	Test pressure	235 PSI (16.0 bar)
4	Temperatures	
	-max. (hot water inlet)	175°F (80°C)
	-recommended (energy saving)	140°F (60°C)
5	Ceramic disc Cartridge	
6	Water connections	hot - left
		cold - right

Note:
High pressure differentials between cold and hot water connectio must be avoided.
We reserve the right to introduce technical changes without noti

MAINTENANCE

Chrome Faucets: Use only liquid cleansers or soapy water. Anti-lime or acidic cleansers such as scouring agents or abrasive sponges are to be **Avoided.** Polish with a soft cloth.
Again, please do not use any abrasive cleansers.
Colored and special finish faucets: Clean only with a cloth and clean water, or a very diluted washing up liquid. Polish as described above f
Again, please do not use any abrasive cleansers.

03.05

WHITEHAUS

Whitehaus Collection
589 Orange Avenue West Haven CT 06516
Tel. 1-800-527-6690

WHITEHAUS

GalleryHaus



3-4012/3-4045