


PLASTIC DRUM STANDARD PRODUCT DESCRIPTION

Product Specification Number: PGP55X-XX-XX-XX-XX-XX		Product Name: GP-55			
Regulatory Information: un 1H1/Y1.9/150 (Test Report P108) un 1H1/Y1.4/150 with vent (Test Report P102) un 1H1/Y1.2/100 (Test Report P152)	Bill of Materials: Body: GP-55, extrusion blow molded high molecular weight high density polyethylene (HMW-HDPE) Fittings: 2" BTR and 2" NPS. Vented bungs are available as an option. 56X4 European BTR available. (BTR = Buttress, NPS = National Pipe Straight thread)	Product Illustration: 			
Nominal Capacity: 55.0 U.S. Gallons	Outage: 2.2 U.S. Gallons	Overall Height: 34.8 inches	Total Weight: 21.0 lbs.		
Actual Capacity: 57.2 U.S. Gallons	Outage %: 4.0 %	Body Height: 34.8 inches	Body Weight: 20.8 lbs.		
Export Cubes: 10.41 cu. ft.	Nominal O.D.: 23.3 inches	Mid Panel Height: 10.3 inches	Min. wall thickness: 0.090 inches		
Special Notes:					
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> <p>1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.</p> <p>2) Drums may be stacked 3 high (1+2) maximum with pallets between drums. For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each. For vented drums, maximum top load on bottom drums not to exceed 1400 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.</p> </td> <td style="width: 50%; vertical-align: top;"> <p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Fits four wide in standard trailer.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> <p>7) Test Report P152, drum is manufactured with 100% in-process regrind available from Mt. Sterling.</p> </td> </tr> </table>				<p>1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.</p> <p>2) Drums may be stacked 3 high (1+2) maximum with pallets between drums. For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each. For vented drums, maximum top load on bottom drums not to exceed 1400 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.</p>	<p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Fits four wide in standard trailer.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> <p>7) Test Report P152, drum is manufactured with 100% in-process regrind available from Mt. Sterling.</p>
<p>1) Maximum filling temperature 150 F. When filled at this recommended maximum filling temperature drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.</p> <p>2) Drums may be stacked 3 high (1+2) maximum with pallets between drums. For nonvented drums, maximum top load on bottom drums not to exceed 2000 lbs each. For vented drums, maximum top load on bottom drums not to exceed 1400 lbs each. Pallets should be of good quality that provides adequate support for plastic drums.</p>	<p>3) Handle with parrotbeak, side grabber, and sling.</p> <p>4) Fits four wide in standard trailer.</p> <p>5) Recycle symbol embossed on bottom.</p> <p>6) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.</p> <p>7) Test Report P152, drum is manufactured with 100% in-process regrind available from Mt. Sterling.</p>				
<p>Data, dimensions, and information provided on this document are considered as nominal values for general purpose use in evaluating this product for customer's application. These are not considered as manufacturing specifications. It is the responsibility of the customer or filler to select the appropriate packaging for use or resale, based on all information at their disposal, including specific application, regulatory compliance, product compatibility, transport, storage, and material handling requirements. Regulatory compliance for remanufacture, repair, or reuse of packaging is the responsibility of the reconditioner, customer and filler. Refer to appropriate regulations for packaging filling, transport, and storage requirements with your specific product.</p> <p>WE HEREBY DISCLAIM AND EXCLUDE ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.</p>					