



A-VR / A-VRF SERIES

DIFFUSERS



Diffuser can be used for both air intake and exhaust.
 Recommended for ceiling and drop ceiling applications.
 360 degree diffusion pattern.
 The baffle can be rotated to obtain the required air consumption listed in the specifications.
 A-VR Contains no flange. Simple pop-in installation.
 A-VRF diffuser is installed with the use of retaining ring.
 Diffusers are manufactured of ABS 5VA plastic.



Model	Measurements [in.]								
	Ø D	Ø D1	Ø D2	Ø D3	H max	H1	H2	Air pass, Sq.Ft	Damper normal pitch, inch
A 100 VR	3 15/16"	3 5/16"	3 9/16"	5 13/16"	2 9/16"	1 3/4"	1"	0.0648	0...13/16"
A 125 VR	4 15/16"	4 1/8"	4 5/16"	6 9/16"	2 3/4"	1 9/16"	13/16"	0.0861	0...7/8"
A 150 VR	5 7/8"	4 15/16"	5 1/16"	7 7/8"	3 1/8"	1 15/16"	1 3/16"	0.0968	0...7/8"
A 200 VR	7 7/8"	6 15/16"	5 1/16"	9 11/16"	3 1/8"	2 1/16"	1 5/16"	0.0861	0...3/4"

Model	Measurements [in.]						
	Ø D	Ø D1	Ø D2	H	H1	Air pass, Sq.Ft	Damper normal pitch, inch
A 100 VRF	3 15/16"	3 9/16"	5 13/16"	2 5/16"	1 1/8"	0.0648	0...13/16"
A 125 VRF	4 15/16"	4 5/16"	6 9/16"	2 5/16"	13/16"	0.0861	0...7/8"
A 150 VRF	5 7/8"	5 1/16"	7 7/8"	2 5/16"	13/16"	0.0968	0...7/8"
A 200 VRF	7 7/8"	5 1/16"	9 11/16"	2 5/16"	13/16"	0.0861	0...3/4"
A 200/150 VRF	5 7/8"	5 1/16"	9 11/16"	3 1/4"	13/16"	0.0861	0...3/4"

Product can be viewed at VentsUS.com/cat/631