



# Interior Latex Flat Ceiling Paint GC1070

9 FINISHES  
PAINTING (09900)

## DESCRIPTION

This interior ceiling paint is formulated to provide minimal spatter and excellent coverage. It hides minor surface imperfections and dries quickly to a smooth, even finish.

## FEATURES

- Spatter free
- Uniform finish
- Easy to apply

## COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

## SPECIFICATION DATA

### Color:

Ceiling white

### Finish: Eggshell

Flat, 2.5 - 6.5 units @ 85°

### Clean-up Solvent:

Soap and water

### Density:

10.91 lbs/gal (1.31 kg/L)

### VOC:

50 g/L (0.42 lbs/gal) maximum

### Solids:

Volume - 26% +/- 1%

Weight - 42% +/- 1%

### Practical Coverage:

Apply at 200 - 300 sq ft/gal (5-7 m<sup>2</sup>/L).

Actual coverage may vary depending on substrate and application method.

### Recommended Film Thickness:

4.0 - 8.0 mils wet

1.3 - 1.9 mils dry

### Flame Spread Rating:

Class A (0-25) on non-combustible surfaces

### Flash Point:

None

### Dry Time 77°F (25°C) & 50% RH:

To touch - 1 hour

To recoat - 4 hours

### Shelf Life:

1 year minimum - unopened



9 FINISHES  
PAINTING (09900)

## SURFACE PREPARATION

Clean and dry all surfaces to remove any dirt, dust, grease, wax, loose or peeling paint. Dull glossy surfaces by sanding or using a surface conditioner. Patch all cracks and holes with a patching compound; sand and prime before painting. Prime unpainted wood, metal, drywall or plaster with the appropriate **GLIDDEN™** primer.

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## DIRECTIONS FOR USE

### RECOMMENDED TOOLS:

Apply with a quality 1/4" – 3/8" nap roller, a nylon or polyester brush or a paint pad. An extension pole is recommended for making longer strokes; making it easier to maintain a wet-edge.

### APPLICATION:

Mix thoroughly before use. Apply at package consistency. Thinning not normally required. For airless spray, use a .015"-.019" tip at 2000 psi, adjust pressure as needed. Apply generously and avoid overspreading. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

1. Stir paint thoroughly with a lifting motion to insure uniform color.
2. Prepare roller by dampening it slightly with water.
3. Brush or edge a 3" or 4" border around the edge of the ceiling.

4. Start with the short dimension of the ceiling. Paint across one end of the room first, doing a strip wide enough to suit your reach. Go back to the starting edge and paint another strip parallel to the first working gradually over the entire length of the room.
5. To reduce lap marks and ensure that you do not miss any areas, try to keep the light source at your back and start by painting away from the window. If there is more than one window, choose the largest window.

### CLEAN-UP AND CARE FOR THE PAINTED SURFACE:

Clean hands and tools with warm, soapy water. Wipe up spills immediately with damp cloth. Painted surfaces may be washed after 30 days with mild detergent and cellulose sponge. Do not use harsh, abrasive cleaners.

## PRECAUTIONS

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS6-0506

## SHIPPING

### FREIGHT CLASSIFICATION:

Paint, Freezable

### PACKAGING:

1 gallon ( 3.785 L)  
5 gallons (18.925 L)

### FLASH POINT:

None



Akzo Nobel Paints LLC, Strongsville, Ohio 44136



1-800-GLIDDEN • www.glidden.com

**LIMITATION OF LIABILITY** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.