

NOVA53



31.5" x 60.75" x 27.25" (H x W x D)

Flat top commercial ice cream freezer with sliding glass lid, digital thermostat, novelty baskets, and 17.8 cu.ft. capacity

Highlights:

Digital controls offer easy and intuitive temperature management

Baskets included for convenient storage

Commercially listed to NSF-7 standards

Product Features:

Commercially approved	UL-S listed to NSF-7 Standards for use in commercial establishments
Digital thermostat	Electronic controls for more precise temperature management
Wide temperature range	Digital thermostat can be set between -13 and +23°F to accommodate a variety of frozen treats
Baskets included	Four epoxy-coated wire baskets included to store novelty items
Sliding glass lid	Two tempered glass lids glide smoothly for easy use
Strong insulation	3" thick insulation helps to ensure items stay cold
Manual defrost	Static cooling system for improved temperature stability
Removable lock	A keyed lock is included for optional use
Steel interior	Durable construction in a white finish for easy visibility








NOVA53 Specifications:

Height of Cabinet 31.5" (80 cm) Width 60.75" (154 cm) Depth 27.25" (69 cm) Capacity 16.6 cu.ft. (470 L) Defrost Type Manual Door Glass Cabinet White US Electrical Safety UL Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz Weight 150.0 lbs. (68 kg)
Depth 27.25" (69 cm) Capacity 16.6 cu.ft. (470 L) Defrost Type Manual Door Glass Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Capacity 16.6 cu.ft. (470 L) Defrost Type Manual Door Glass Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Defrost Type Manual Door Glass Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Door Glass Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Cabinet White US Electrical Safety ULC Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
US Electrical Safety Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency UL S Voltage/Frequency
Canadian Electrical Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Safety Sanitation UL-S Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Amps 4.2 Voltage/Frequency 115 V AC/60 Hz
Voltage/Frequency 115 V AC/60 Hz
Weight 150.0 lbs. (68 kg)
Shipping Weight 157.0 lbs. (71 kg)
Estimated Time to Ship Next day shipping
Parts & Labor Warranty 1 Year
Compressor Warranty 5 Years
Freezer
Door Swing Sliding
Interior Height 26.0" (66 cm)
Interior Width 54.5" (138 cm)
Interior Depth 21.0" (53 cm)
Thermostat Type Digital
Refrigerant Type R290a
Refrigerant Amount 3.17 oz.
High Side PSI 345.0
Low Side PSI 140.0
Compressor Step Height 9.75" (25 cm)
Compressor Step Width 7.88" (20 cm)
Compressor Step Depth 21.0" (53 cm)
Temperature Range -13 to 23°F



ELEC. CORD