

## **Single Control Kitchen Faucet** With Pull Down Spray

LIMITED LIFETIME WARRANTY



# **Before You Begin**

Check to make sure you have the following:

# **Tools and Supplies**

You will need the following to install your new faucet:

Phillips



Adjustable

Wrench Screwdriver

Silicone Sealant

10663 10665

## **Faucet Installation**

#### Shut off main water supply before installation.



Unscrew screws on lock nut. Remove the lock nut from the faucet body.



**2** Install faucet through center hole.



**3** Slide rubber washer and metal washer onto shank. Secure shank with lock nut.



4 Connect and tighten the water supply line nuts with wrench.



**5** Remove the protective cap from the outlet port prior to pushing the hose adapter onto the same port, you will hear a "click" sound once they are joined.



6 Attach the weight to cover the weight locator label on the spray hose.



7 After installing faucet, remove sprayhead and turn on water to remove any left over debris. Re-assemble sprayhead.

## Troubleshooting Guide

Minor problems often can be fixed without a plumber. Before doing any work on the faucet, shut off water supply and close stopper or drain to avoid losing small parts.

Problem	Cause	Solution
Leaks underneath handle.	Locking nut has come loose. O-ring on cartridge is dirty or damaged.	Tighten the locking nut. Clean or replace O-ring.
Hose does not retract.	Metal weight is not installed in the appropriate position.	Reinstall metal weight.
There are leaks from the hose underneath the deck.	Hose and spray head connection may be loose.	Tighten the connection between the spray head and hose.

### **Replacement Parts**

Keep this manual for ordering replacement parts.



	Index Button	A66D558
2	Metal Handle	A079086
3	Handle Trim Cap	A103121
ŀ	Adjusting Ring	A104332
)	Ceramic Disc Cartridge	A507906N-31
6	Cover Plate Assembly	A667003-S
,	Hose Adapter	A663123N
3	Pull-Down Spray Head	A568009N
)	Spray Hose	A515111WCP
0	Weight	A504103ZN
1	Mounting Hardware	A603171