TECHNICAL DATA

RUD

KRUD KUTTER[®] GRAFFITI REMOVER

DESCRIPTION AND USES

Krud Kutter[®] Graffiti Remover is a proprietary blend of biodegradable surfactants, detergents and emulsifiers that is designed to remove dried paints and stains on a variety of surfaces. It removes acrylic and acrylic enamel, aerosol paint, alkyd and polyurethane enamels, oil-based lacquers, primers, sealers, water-based enamels and also removes permanent markers, ink, lipstick, crayon and shoe dye.

Graffiti Remover is suitable for use on aluminum, brick, cinder block, concrete, fiberglass, formica, glass, metals, plastic, CMU, stainless steel, street signs, stucco, tile, terrazzo and vinyl.

IMPORTANT: Test first on an inconspicuous area. May dull some painted surfaces. Not recommended for use on non-colorfast materials or woodwork.

PRODUCTSSKUDescriptionGR16416 oz. Trigger SprayerGR22622 oz. Trigger SprayerGR32632 oz. Trigger SprayerGR0121-Gallon BottleGR055-GallonsGR5555-Gallon Drum

PRODUCT APPLICATION

DIRECTIONS FOR HARD & SOFT SURFACES SUCH AS SIGNS & VINYL:

Thoroughly spray area damaged by graffiti and wait 3-5 minutes. Wipe off with a clean cloth or towel. Repeat if necessary.

DIRECTIONS FOR POROUS SURFACES SUCH AS CONCRETE & BRICK:

Thoroughly spray area damaged by graffiti and wait 5-10 minutes. Use a brush to agitate and loosen graffiti. Hose off with water or use pressure washer. Repeat if necessary.

WARNING: MAY BE HARMFUL IF INHALED, ABSORBED THROUGH THE SKIN OR SWALLOWED.

Mist or vapors may be irritating to the eyes, nose, throat and lungs. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

KEEP OUT OF REACH OF CHILDREN.



TECHNICAL DATA

KRUD KUTTER[®] GRAFFITI REMOVER

PHYSICAL PROPERTIES

	GRAFFITI REMOVER
Composition	Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
Color	Clear
рН	NA
VOC	9%
Practical Coverage	16 ounces – 25-37 square feet
	22 ounces – 35-50 square feet
	32 ounces – 50-75 square feet
	1-Gallon – 200-300 square feet
Shelf Life	NA
Flash Point	200°F (93°C)
Caution!	WARNING: MAY BE HARMFUL IF INHALED, ABSORBED THROUGH THE SKIN OR SWALLOWED. Mist or vapors may be irritating to the eyes, nose, throat and lungs. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. KEEP OUT OF REACH OF CHILDREN.
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061 An RPM Company

Phone: 877•385•8155 www.rustoleum.com