

# SAFETY DATA SHEET

Issuing Date 15-Jun-2015

Revision Date 13-Apr-2016

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name E91BP-4, E91BP-4UP, E91BP-8, E91BP-12, E91BP-20W

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Alkaline battery

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name Energizer Battery

Supplier Address 533 Maryville University Drive  
St. Louis  
MO  
63141  
US

Supplier Phone Number Phone:314-985-2000

Supplier Email travisr.stevener@energizer.com

### Emergency telephone number

Company Emergency Phone Number 314-985-1500

## 2. HAZARDS IDENTIFICATION

### Classification


This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.



Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Gases)	Category 2
Acute toxicity - Inhalation (Vapors)	Category 2
Acute toxicity - Inhalation (Dusts/Mists)	Category 2
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive Toxicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>
<p><b>Hazard Statements</b>                  Harmful if swallowed                  Fatal if inhaled                  Causes severe skin burns and eye damage                  May cause an allergic skin reaction                  May cause cancer                  May damage fertility or the unborn child                  May cause respiratory irritation. May cause drowsiness or dizziness</p>	
	
<p>This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.</p>	
<b>Appearance</b> Silver	<b>Physical state</b> Solid
<b>Odor</b> None	

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Do not breathe dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Wear respiratory protection
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves

**Precautionary Statements - Response**

- Specific treatment is urgent (see .? on this label)
- Immediately call a POISON CENTER or doctor/physician



Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor/physician

**Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
If skin irritation or rash occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Immediately call a POISON CENTER or doctor/physician  
Call a POISON CENTER or doctor/physician if you feel unwell

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
Rinse mouth  
Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

6 % of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Very toxic to aquatic life with long lasting effects  
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

**Interactions with Other Chemicals**

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Manganese dioxide	1313-13-9	30 - 60	*
Zinc	7440-66-6	10 - 30	*
Steel manufacture, chemicals	65997-19-5	10 - 30	*
Potassium hydroxide	1310-58-3	5 - 10	*
Graphite	7782-42-5	3 - 7	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES



**First aid measures****General Advice**

This is a battery. In case of rupture: Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.

**Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice. May cause an allergic skin reaction.

**Inhalation**

Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur. Do not breathe dust.

**Ingestion**

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Self-protection of the first aider**

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Do not breathe dust. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

**Most important symptoms and effects, both acute and delayed****Most Important Symptoms and Effects**

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

**Indication of any immediate medical attention and special treatment needed****Notes to Physician**

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitization in susceptible persons. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. Product is or contains a sensitizer. May cause sensitization by skin contact.

### Explosion Data

**Sensitivity to Mechanical Impact**      None.

**Sensitivity to Static Discharge**      None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not breathe dust.

#### **Other Information**

Refer to protective measures listed in Sections 7 and 8.

### Environmental precautions

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

### Methods and material for containment and cleaning up

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for cleaning up**

Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### Handling

In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

### Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

#### Incompatible Products

Acids. Bases. Oxidizing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m <sup>3</sup> Mn TWA: 0.1 mg/m <sup>3</sup> Mn	(vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn TWA: 1 mg/m <sup>3</sup> Mn STEL: 3 mg/m <sup>3</sup> Mn
Zinc 7440-66-6	STEL: 10 mg/m <sup>3</sup> respirable fraction TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume
Steel manufacture, chemicals 65997-19-5	STEL: 10 mg/m <sup>3</sup> Zr TWA: 0.05 mg/m <sup>3</sup> Pb TWA: 0.00005 mg/m <sup>3</sup> Be inhalable fraction TWA: 1 mg/m <sup>3</sup> Cu dust and mist TWA: 0.2 mg/m <sup>3</sup> Se TWA: 1 mg/m <sup>3</sup> Y TWA: 5 mg/m <sup>3</sup> Zr TWA: 0.02 mg/m <sup>3</sup> Mn TWA: 0.1 mg/m <sup>3</sup> Mn TWA: 0.5 mg/m <sup>3</sup> Hf S*	TWA: 50 µg/m <sup>3</sup> Pb TWA: 2 µg/m <sup>3</sup> Be TWA: 0.2 mg/m <sup>3</sup> Se TWA: 5 mg/m <sup>3</sup> Zr Action Level: 30 µg/m <sup>3</sup> Pb Poison, See 29 CFR 1910.1025 (vacated) TWA: 2 µg/m <sup>3</sup> Be (vacated) TWA: 0.2 mg/m <sup>3</sup> Se (vacated) TWA: 5 mg/m <sup>3</sup> Zr (vacated) STEL: 25 µg/m <sup>3</sup> 30 min (vacated) STEL: 10 mg/m <sup>3</sup> Zr (vacated) Ceiling: 5 µg/m <sup>3</sup> (vacated) Ceiling: 5 mg/m <sup>3</sup> Ceiling: 5 µg/m <sup>3</sup> Be Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 4 mg/m <sup>3</sup> Be IDLH: 100 mg/m <sup>3</sup> Cu dust and mist IDLH: 500 mg/m <sup>3</sup> Mn IDLH: 1 mg/m <sup>3</sup> Se IDLH: 500 mg/m <sup>3</sup> Y IDLH: 25 mg/m <sup>3</sup> Zr IDLH: 100 mg/m <sup>3</sup> Pb IDLH: 10 mg/m <sup>3</sup> Ni IDLH: 50 mg/m <sup>3</sup> Hf Ceiling: 0.05 mg/m <sup>3</sup> V dust and fume 15 min Ceiling: 0.0005 mg/m <sup>3</sup> Be TWA: 1 mg/m <sup>3</sup> Cu dust and mist TWA: 1 mg/m <sup>3</sup> Mn TWA: 0.2 mg/m <sup>3</sup> except Selenium hexafluoride Se TWA: 1 mg/m <sup>3</sup> Y TWA: 5 mg/m <sup>3</sup> except Zirconium tetrachloride Zr TWA: 0.050 mg/m <sup>3</sup> Pb TWA: 0.015 mg/m <sup>3</sup> except Nickel carbonyl Ni TWA: 0.5 mg/m <sup>3</sup> Hf STEL: 3 mg/m <sup>3</sup> Mn STEL: 10 mg/m <sup>3</sup> Zr
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m <sup>3</sup>	(vacated) Ceiling: 2 mg/m <sup>3</sup>	Ceiling: 2 mg/m <sup>3</sup>
Graphite 7782-42-5	TWA: 2 mg/m <sup>3</sup> respirable fraction all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust

		(vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	
--	--	---	--

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

**Appropriate engineering controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Face protection shield.

**Skin and body protection** Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. Do not breathe dust.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical state</b>	Solid	<b>Odor</b>	None
<b>Appearance</b>	Silver	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		



<b>Lower flammability limit</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Specific Gravity</b>	No data available	None known
<b>Water Solubility</b>	Insoluble in water	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known
<b>Explosive properties</b>	No data available	
<b>Oxidizing properties</b>	No data available	

**Other Information**

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Exposure to air or moisture over prolonged periods. Excessive heat.

**Incompatible materials**

Acids. Bases. Oxidizing agent.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.

**Inhalation**

Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Fatal if inhaled.



<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed.

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Manganese dioxide 1313-13-9	= 9000 mg/kg ( Rat )	-	-
Potassium hydroxide 1310-58-3	= 284 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization in susceptible persons. May cause sensitization by skin contact.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Steel manufacture, chemicals 65997-19-5	A1 A3	Group 1 Group 2A Group 2B Group 3	Known Reasonably Anticipated	X

**Reproductive toxicity** Contains a known or suspected reproductive toxin.

**STOT - single exposure** No information available.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

**Chronic Toxicity** Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may

cause chronic conditions. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects.

**Target Organ Effects**

Eyes. Respiratory system. Skin. Gastrointestinal tract (GI). Systemic Toxicity. Reproductive System.

**Aspiration Hazard**

No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

307.00 mg/kg

**ATEmix (inhalation-gas)**

435.00 ppm (4 hr)

**ATEmix (inhalation-dust/mist)**

0.21 mg/l

**ATEmix (inhalation-vapor)**

2.00 ATEmix

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas)		48h EC50: 0.139 - 0.908 mg/L
Potassium hydroxide 1310-58-3		96h LC50: = 80 mg/L (Gambusia affinis)		

### Persistence and Degradability

No information available.

### Bioaccumulation

No information available

Chemical name	Log Pow
Manganese dioxide 1313-13-9	<0
Potassium hydroxide 1310-58-3	0.83

### Other adverse effects

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated Packaging**

Do not reuse empty containers.

**California Hazardous Waste Codes 141**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Zinc 7440-66-6	Ignitable powder Toxic
Steel manufacture, chemicals 65997-19-5	Toxic
Potassium hydroxide 1310-58-3	Toxic Corrosive

**14. TRANSPORT INFORMATION**

**DOT**  
 Proper Shipping Name NOT REGULATED  
 Hazard Class NON REGULATED  
 N/A

**TDG** Not regulated

**MEX** Not regulated

**ICAO** Not regulated

**IATA**  
 Proper Shipping Name Not regulated  
 Hazard Class NON REGULATED  
 N/A

**IMDG/IMO**  
 Hazard Class Not regulated  
 N/A

**RID** Not regulated

**ADR** Not regulated

**ADN** Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**



TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Manganese dioxide - 1313-13-9	1313-13-9	30 - 60	1.0
Zinc - 7440-66-6	7440-66-6	10 - 30	1.0
Steel manufacture, chemicals - 65997-19-5	65997-19-5	10 - 30	1.0
			0.1

#### **SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	No
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc 7440-66-6		X	X	
Steel manufacture, chemicals 65997-19-5		X		
Potassium hydroxide 1310-58-3	1000 lb			X

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Zinc 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

### US State Regulations

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

#### **U.S. State Right-to-Know Regulations**

This product does not contain any substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois



Zinc 7440-66-6	X	X	X	X	
Potassium hydroxide 1310-58-3	X	X	X	X	
Manganese dioxide 1313-13-9			X	X	X
Graphite 7782-42-5	X	X	X		

### International Regulations

Chemical name	Carcinogen Status	Exposure Limits
Manganese dioxide		Mexico: TWA= 0.2 mg/m <sup>3</sup>
Steel manufacture, chemicals	A3 A2	Mexico: TWA 0.15 mg/m <sup>3</sup> Mexico: TWA 0.002 mg/m <sup>3</sup> Mexico: TWA 0.2 mg/m <sup>3</sup> Mexico: TWA 5 mg/m <sup>3</sup> Mexico: STEL 10 mg/m <sup>3</sup>
Graphite		Mexico: TWA= 2 mg/m <sup>3</sup>

### Canada

#### WHMIS Hazard Class

Not determined

## 16. OTHER INFORMATION

<b>NFPA</b>	<b>Health Hazards</b> 1	<b>Flammability</b> 0	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> -
<b>HMIS</b>	<b>Health Hazards</b> 0	<b>Flammability</b> 0	<b>Physical Hazard</b> 0	<b>Personal Protection</b> X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 15-Jun-2015  
**Revision Date** 13-Apr-2016  
**Revision Note** No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

