

ACCLAIM 1500 Cherokee Parkway, Suite 100, Acworth, GA 30102 P: 866-845-5451 • F: 866-816-6165 E: service@acclaim-lighting.com • www.acclaim-lighting.com

INTERIOR • OUTDOOR

IN21176 **INSTALLATION INSTRUCTIONS**

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. Connect the stems (16)(15)(14), screw them into the nipple (17) and thread the stems into the swivel (13).
- 2. Install bulbs: (bulbs not included)
- (Do not exceed the maximum capacity recommended on the sockets).
- 3. Place the iron washer (19) first, then plastic washer (20) over the arm (18).
- 4. Place glass shade (21) over the arm (18).
- 5. Place plastic washer (22), then iron washer (23) over the arm (18) and secure with the hex nut (24). Place the cap (25)over the arm (18) and secure with the finial (26).
- 6. Thread two machine screws (6) to the mounting plate (7) and secure with the hex nut (9).
- 7. Secure the mounting plate (7) with mounting screw (10) to the outlet box (1).
- 8. Pull out the outlet wire and ground wire from the outlet box (1). Make wire connections. --Ribbed wire (w/o marking) from light to White wire (2) from power source.
- --Smooth wire (w/o marking) from light to Black wire (4) from power source.
- --Loop the ground wire (3) to mounting plate (7) with a ground screw (8).
- 9. Attach the fixture canopy (11) against the outlet box (1), secure with the ball nut (12).





1. OUTLET BOX 2. WHITE WIRE 3. GROUND WIRE 4. BLACK WIRE 5. WIRE CONNECTOR 6. MACHINE SCREW 7. MOUNTING PLATE 8. GROUND SCREW 9. HEX NUT **10. MOUNTING SCREW** 11. CANOPY 12 BALL NUT 13. SWIVEL 14. STEM **15. STEM 16. STEM 17. NIPPLE** 18. ARM **19. IRON WAHER 20. PLASTIC WASHER** 21. GLASS SHADE 22. PLASTIC WAHSER 23. IRON WASHER 24. HEX NUT 25. CAP 26. FINIAL