

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ZAR WOOD PATCH – ALL COLORS
PRODUCT CODE: 304, 309,310, 314

HMS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATON

MANUFACTURE'S NAME: UNITED GILSONITE LABORATORIES
ADDRESS: 1396 JEFFERSON AVENUE
SCRANTON, PA 18509

EMERGENCY PHONE: (800) 424-9300
INFORMATION PHONE: (570) 344-1202
NAME OF PREPARER: R. BARAKO

DATE REVISED: APRIL 2013
SUPERSEDES: JUNE 2010

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mmHg@TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
WATER	7732-18-5	NOT ESTAB	NOT ESTAB	NOT ESTAB	1.0 (68F)	23
CALCIUM CARBONATE	1317-65-3	5MG/M ³ (RESP)	2 MG/M ³ (RESP)	NOT ESTAB	N/A	48
POLYVINYL ACETATE RESIN	9003-20-7	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	5
NEPHELINE SYENITE	37244-96-5	5 MG/M ³ (RESP)	NOT ESTAB	10 MG/M ³ (TWA)	N/A	16
MICA	12001-26-2	3 MG/M ³ (RESP)	3 MG/M ³ (RESP)	NOT ESTAB	N/A	3
YELLOW IRON OXIDE	51274-00-1	10 PPM	5 MG/M ³	NOT ESTAB	N/A	1
BURNT UMBER	12713-03-0	NOT ESTAB	10 MG/M ³	NOT ESTAB	N/A	1
BLACK IRON OXIDE	1317-61-9	NOT ESTAB	NOT ESTAB	NOT ESTAB	N/A	1
RED IRON OXIDE	1309-37-1	NOT ESTAB	10 MG/M ³	NOT ESTAB	N/A	1
STODDARD SOLVENT	8052-41-3	100 PPM	100 PPM	100 PPM	3.0 (68F)	1

No toxic chemical (s) subject to the reporting requirements of Section 313 of Title III and of CFR 372 are present

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 (F)
VAPOR DENSITY: HEAVIER THAN AIR
COATING VOC: 0.41 LB/GAL (49 G/L)
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: COLOR PRODUCT SPECIFIC. TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H₂O =1) 1.8
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINER MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32(F) FOR STORAGE. TEMPERATURES BELOW 50(F) FOR APPLICATION.

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, MENTAL CONFUSION DEPENDING ON THE QUANTITY OF MATERIAL INGESTED.

HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION: SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSEY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING.

INHALATION: REMOVE VICTIM TO FRESH AIR.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS.

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING SANDING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50(F) TO 90(F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SANDING DRY FILM, USE NIOSH APPROVED RESPIRATORS FOR DUST PARTICLES.

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II.

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT.

EYE PROTECTION: USE SAFETY EYEWEAR WITH SPLASH GUARDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM.

SECTION IX – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.