SAFETY DATA SHEET



Date of issue/Date of revision 18 October 2016 Version 1

Section 1. Identification		
Product name	: PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3	
Product code	: 00387530	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	
Technical Phone Number	: 1-800-441-9695 (8:00 am to 5:00 pm EST)	

Section 2. Hazards identification	
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1
	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 35.7%
GHS label elements Hazard pictograms	
Signal word Hazard statements <u>Precautionary statements</u>	WarningMay cause an allergic skin reaction.

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 2. Hazards identification

be allowed out of the workplace.
 IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. Photosensitive agents : In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the sources of UV light which may increase the sensitivity of skin.
: Not applicable.
 Dispose of contents and container in accordance with all local, regional, national and international regulations.
: Emits toxic fumes when heated.
: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture	
Product name	: PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3	

Ingredient name	%	CAS number
propane-1,2-diol 4,5-dichloro-2-octyl-2H-isothiazol-3-one		57-55-6 64359-81-5

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Date of issue 18 October 2016 Version 1

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 4. First aid measures

	In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Most important symptoms/	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide

Date of issue 18 October 2016 Version 1

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 5. Fire-fighting measures

Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if	
for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitabl training.	е
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breat apparatus (SCBA) with a full face-piece operated in positive pressure mode.	hing

Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated

Section 7. Handling and storage

from a compatible material, kept tightly closed when not in use. Empty containers retai	Precautions for safe handling	
product residue and can be hazardous. Do not reuse container.	Protective measures :	history of skin sensitization problems should not be employed in any process in which

Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue 18 October 2016 Version 1

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 7. Handling and storage

Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure limits Ingredient name Exposure limits propane-1,2-diol IPEL (PPG). TWA: 10 mg/m³ 4,5-dichloro-2-octyl-2H-isothiazol-3-one None. Key to abbreviations Α = Acceptable Maximum Peak S = Potential skin absorption ACGIH = American Conference of Governmental Industrial Hygienists. SR = Respiratory sensitization С = Ceiling Limit SS = Skin sensitization F STEL = Short term Exposure limit values = Fume = Internal Permissible Exposure Limit IPEL TD = Total dust OSHA = Occupational Safety and Health Administration. TLV = Threshold Limit Value = Respirable TWA = Time Weighted Average R = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances 7 Consult local authorities for acceptable exposure limits. **Recommended monitoring** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of procedures the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. Appropriate engineering : Good general ventilation should be sufficient to control worker exposure to airborne contaminants. controls **Environmental exposure** : Emissions from ventilation or work process equipment should be checked to ensure controls they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Date of issue 18 October 2016 Version 1

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 8. Exposure controls/personal protection

Hygiene measures	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber polyethylene
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Relative density	÷	1.09
Vapor density	4	Not available.
Vapor pressure	1	Not available.
Evaporation rate	1	Not available.
Lower and upper explosive (flammable) limits	1	Upper: 0%
Flammability (solid, gas)	÷	Not available.
Decomposition temperature	3	Not available.
Auto-ignition temperature	1	Not available.
Flash point	1	Closed cup: Not applicable. [Product does not sustain combustion.]
Boiling point	1	100°C (212°F)
Melting point	1	Not available.
рН	1	Not available.
Odor threshold	:	Not available.
Odor	:	Characteristic.
Color	:	Not available.
Physical state	:	Liquid.
Appearance		

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 9. Physical and chemical properties

Density (lbs / gal)	: 9.1
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
Volatility	: 65% (v/v), 59.869% (w/w)
% Solid. (w/w)	: 40.131

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute	toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-		
	LD50 Oral	Rat	20 g/kg	-		
4,5-dichloro-2-octyl-2H- isothiazol-3-one	LD50 Dermal	Rabbit	3.9 g/kg	-		
	LD50 Oral	Rat	2.2 g/kg	-		
Conclusion/Summary	: There are no data available on	the mixture itself				
Irritation/Corrosion						
Conclusion/Summary						
Skin	: There are no data available on the mixture itself.					
Eyes	: There are no data available on the mixture itself.					
Respiratory	: There are no data available on the mixture itself.					
Sensitization						
Conclusion/Summary						

Date of issue 18 October 2016 Version 1

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 11. Toxicological information

	6
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
Mutagenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxic	<u>city (single exposure)</u>
Name	
4 E diablana O actul Ol Liact	

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Potential acute nearth enects	
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.
Delayed and immediate effects	and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Acrylate components of the mixture have irritating properties. Prolonged or repeated contact with skin or mucous membrane may result in irritation symptoms, such as redness, blistering, dermatitis etc. May cause allergic skin reactions with repeated exposure. The inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. Ingestion may cause nausea, weakness and central nervous system effects. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
Short term exposure	

Short term exposure

Category 3

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 11. Toxicological information

Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate	: There are no data available on the mixture itself.
effects	
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	ects
General	 Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
General Carcinogenicity	
	very low levels.
Carcinogenicity	very low levels. No known significant effects or critical hazards.
Carcinogenicity Mutagenicity	very low levels.No known significant effects or critical hazards.No known significant effects or critical hazards.
Carcinogenicity Mutagenicity Teratogenicity	 very low levels. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.
Carcinogenicity Mutagenicity Teratogenicity Developmental effects	 very low levels. No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
propane-1,2-diol	-0.92	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been

United States Page: 9/11

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 13. Disposal considerations

cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

•			
	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.		No. Not applicable.

Additional information

DOT: None identified.IMDG: None identified.IATA: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Product name PPG3103V PPG TIMELESS STAIN & SEALANT IN ONE SOLID COLOR - BASE 3

Section 15. Regulatory information

Name	hazard	Sudden release of pressure		(acute)	Delayed (chronic) health hazard
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	No.	No.	No.	Yes.	No.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 Flammability : 0 Physical hazards : 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)	
Health : 2 Flammability : 0 Instability : 0	
Date of previous issue	: No previous validation
Organization that prepared the MSDS	: EHS
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.