

**Method of Application:**

**Brush:** Apply by brush or roller, use a good brush with natural bristles.

**Roller:** Use Lanco® All Purpose Roller 3/8" Nap PA-566 or conventional or airless spray. Roller application may require special care to prevent bubbling and more than one coat to obtain proper thickness. Apply at 4 mils wet film thickness that will yield 2 mils dry film thickness. With a clean soft varnish brush apply a thin, smooth coat brushing in grain direction. Maintain a wet edge and brush out any lap marks. A second coat, if desired, may be applied without sanding as soon as first coat is dry. If allowed to dry more than 12 hours, sand or buff with fine sandpaper (#220) or steel wood to insure proper adhesion between coats. Remove all dust before varnishing.

**Conventional spray:** For suction feed, use DeVilbiss MBC gun with "E" tip and needle and 30 air cap or equivalent at 35-40 psi atomizing pressure feed. For pressure feed, use DeVilbiss MBC gun with tip and needle and 704 air cap or equivalent at 35-40 psi atomizing pressure and 5-8 psi fluid pressure, 3/8" ID material hose, double regulated pressure tank with oil and moisture separator.

**Airless spray:** Minimum of 28:1 ratio pump, 0.011"-0.013" orifice tip 1/4" ID Teflon material hose.

**Limitation:** Apply in good weather when air and surface temperature are above 40°F and surface temperature is at least 5°F above the dew point. For optimum application properties, material should be between 70° to 100°F prior to mixing and application.

**Note:** When multiple coats of product are applied, be sure to sand lightly between coats with a fine sandpaper and dust clean or vacuum.

**Cleanup:** Wipe up drips and spatters with Lanco® Mineral Spirits MS-107. Clean all equipment with this solution.

**Caution:** Do not take internally. Close container after each use. Keep out of the reach of children. Combustible; keep away from heat and open flame. Avoid prolonged contact with skin and breathing vapors or spray mist.

**Danger / Warning:**

**Precaution:** Flammable mixture, do not use near fire or flame.

**Contains:** Petroleum distillates. Use only with adequate ventilation. Avoid prolonged or repeated breathing of vapor.

It is important to use adequate ventilation as high vapor concentration may cause unconsciousness or even asphyxiation. Ventilation must be sufficient to limit exposure below MSDS limits. Eye irritation and dizziness are indications of over exposure.

Refer to Lanco® material safety data sheet.

Provide adequate ventilation during application and drying cycles. Do not take internally. Swallowing may cause injury, illness or death. If swallowed, do not induce vomiting. Call a physician immediately.

**Notice:** Reports have associated repeated and prolonged occupational over exposure to solvents, with permanent brain and nervous system damage, peripheral nervous tissue damage and liver abnormalities. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Always wear respiratory protection (NIOSH, MSHA TC 23C OR equivalent). Keep out of reach of children.

