

1. What do I need to know about my roof before ordering a skylight?

- Roof pitch - to determine proper skylight, as curb mount requires 0 (flat) - 60 degree pitch
- Roofing material - for appropriate flashing, ECL - shingles (10 - 60 degree pitch) or ECW - tile (14 - 60 degree pitch)
- Rafter spacing - 16" on center, or 24" on center (for example) to determine proper skylight width

2. How do I determine which curb mount skylight size I should order?

- Outside curb dimensions, including flashing, is the correct way to determine the curb mount skylight size you need. It's very important to confirm your curb dimensions before ordering.

3. Is flashing really necessary?

- Yes, VELUX curb mount flashing is required for the "No Leak" installation warranty. This skylight model includes ECL flashing for installation on a low-profile shingle, shake, or slate roof.

4. Can a curb mount skylight be installed on a flat roof?

- Yes, VELUX curb mount skylights can be installed on a roof pitch anywhere between 0 - 60 degrees. Please note: VELUX flashing kits can only be used on a sloped roof.

5. Can I replace a plastic bubble skylight with a VELUX curb mount skylight?

- Yes, VELUX curb mount skylights are perfect for replacing plastic bubble skylights, or any other curb mount skylight.

6. Do I need anything additional on the exterior to install this curb mount skylight?

- In a new installation, you will need 2x4 or 2x6 lumber to build the roof curb on which the skylight is mounted. When replacing an existing skylight, if the curb is in good shape, then you may be able to re-use the existing curb, or you can simply build a new one.