

**Material Safety Data Sheet**

IDENTITY (As Read on Label and Line)  LR1130G Alkaline button Cell	Notice: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

**Section I**

Manufacturer's Name Golden Power Corporation (HK) Ltd.	Telephone Number (852) 3125 2288
Address (Number, Sheet, City, State, and ZIP Code)  Flat C, 20/F., Block 1, Tai Ping Industrial Centre, 57 Ting Kok Road, Tai Po, N.T., Hong Kong	Fax Number (852) 3125 2000 / 3125 2001
	Date Prepared <b>March 01, 2011</b>
	Signature of Preparer (optional)

**Section II – Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Names)	(contents, %/wt)	CAS No.
Manganese Dioxide (MnO <sub>2</sub> )	22.0 %	1313-13-9
Zinc (Zn)	10.0 %	7440-66-6
Potassium Hydroxide (KOH)	3.0 %	1310-58-3
Graphite (C)	2.0 %	7782-42-5
Cadmium (Cd)	≤ 0.0005 %	7440-43-9
Mercury (Hg)	≤ 0.0001 %	7439-97-6
Lead (Pb)	≤ 0.002 %	7439-92-1

**Section III – Physical/Chemical Characteristics**

Boiling Point KOH aqua solution = 140 °C	Specific Gravity (H <sub>2</sub> O=1) MnO <sub>2</sub> = 4.4, Zn = 7.1, KOH = 2.0
Vapor Pressure (mmHg) KOH aqua solution = 3mmHg at 20 °C	Melting Point MnO <sub>2</sub> decompose at 535 °C Zn = 420 °C, KOH aqua = -35 °C
Vapor Density (Air = 1)	Evaporation Rate (Butyl Acetate = 1)

Solubility in Water KOH – complete

Appearance and Color

MnO<sub>2</sub> is a black powder, Graphite is also a black powder, Zinc is a silver metal.  
KOH aqua is a colorless liquid with stimulative order.

**Section IV – Fire and Explosion Hazard Data**

Flash Point (Method Used) Incombustible	Flammable Limits Not Available	LEL	UEL
--	-----------------------------------	-----	-----

Extinguishing Media: See Special Fire Fighting Procedure

Special Fire Fighting Procedure: In case of fire in an adjacent area, use water, CO<sub>2</sub> or dry chemical extinguishers if cells are packed in their original containers since the fuel of the fire is basically paper products. For bulk quantities of unpackaged cells use LITH-X (Graphite Base). In this case, do not use water.

As with any fire, wear self-contained breathing apparatus to avoid inhalation of hazardous decomposition products.

Unusual Fire and Explosion Hazards



**Section V – Reactivity Data**

Stability	Unstable		Conditions to Avoid Do not short circuit, charge or dispose of in fire.
	Stable	√	

Incompatibility (Materials to Avoid)      Hazardous polymerization will not occur.

Hazardous Decomposition or Byproducts      Not Available

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	√	

**Section VI – Health Hazard Data**

Route(s) of Entry.	Inhalation?	Yes	Skin?	Yes	Ingestion?	Yes
--------------------	-------------	-----	-------	-----	------------	-----

Health Hazards (Acute and Chronic)      These chemicals are contained in a sealed can. Risk of exposure occurs, only if battery is mechanically or electrically abused. The most likely risk is acute exposure when a cell vents KOH is caustic alkali and attack the skin and eyes. Contact of electrolyte with skin and eyes should be avoided.

**Section VII – Ecological Information**

Cardnogenicity	NTP?	Not Available	IARC Monographs?	Not Available	OSHA Regulated?	Not Available
----------------	------	---------------	------------------	---------------	-----------------	---------------

Signs and Symptoms of Exposure      KOH can cause chemical burn upon contact with skin.

Medical Conditions  
Generally Aggravated by Exposure      An acute exposure will not generally aggravate any medical help.

**Section VIII –Emergency and First Aid Procedures**

In case of skin contact with content of battery, flush immediately with water.  
For eye contact, flush with copious amount of water for 10 minutes. If imitation persists, get medical help.

**Section IX - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled      Wipe out by wet duster.

**Section X - Waste Disposal Method**

General abandonment

**Section XI - Precautions to Be Taken in Handling and Storing**

Avoid mechanical or electrical abuse.

**Section XII - Other Precautions**

Do not short circuit, charge or dispose of in fire. Battery may explode or leak.

**Section XIII - Control Measures**

Respiratory Protection (Specify Type)      Not Available

Ventilation	Local Exhaust	Special
	Not Available	Not Available
	Mechanical (General)	Other
	Not Available	Not Available

Protective Gloves      Butyl      Eye Protection      Safety Glasses

Other Protective Clothing or Equipment      Not Available

Work / Hygienic Practices      Not Available

**Section XIV – Regulatory Information**

Not Available



---

**Section XV – Other Information**

---

Not Available

---

---

**Section XVI – Transportation Information**

---

Golden Power batteries are considered to be “dry cell” batteries and are not regulated for purposes of transportation with reference to requirements of

1. U.S. Department of Transportation (DOT), Special Provision 130, i.e. “Batteries, dry are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (for example, by the effective insulation of exposed terminals)”.
2. International Civil Aviation Administration (ICAO) and International Air Transport Association (IATA), Special Provision A123, i.e. “An electrical battery or battery powered device having the potential of dangerous evolutions of heat that is not prepared so as to prevent a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or in the case of equipment, by disconnection of the battery and protection of exposed terminals) is forbidden from transportation.”
3. International Maritime Dangerous Goods Regulations (IMDG), Special Provision 304, i.e. “Batteries, dry, containing corrosive electrolyte which will not flow out of the battery case is cracked are not subject to the provisions of this Code provided the batteries are securely packed and protected against short-circuits.

Examples of such batteries include alkali-manganese, silver oxide, zinc carbon, nickel metal hydride and nickel-cadmium batteries.

---