



FELTBUSTER™

HIGH-TRACTION SYNTHETIC ROOFING FELT

Description:

Quality roofing underlayment is critical for helping to prevent wind-driven rain from infiltrating under the roof's shingles and potentially damaging the home's structure and interior. Traditional asphalt felt underlayments tear easily and absorb moisture, leading to wrinkling that telegraphs through the shingles. Competitively priced with typical #15 and #30 asphalt felts, GAF's FeltBuster™ High-Traction Synthetic Roofing Felt is virtually untearable and will not absorb moisture, helping to prevent wrinkling. Its specially designed surface combines enhanced walkability with a cooler working surface (vs. typical black asphalt felts).

Use:

FeltBuster™ High-Traction Synthetic Roofing Felt is for use with asphalt shingles. **Important:** **Always** install FeltBuster™ High-Traction Synthetic Roofing Felt using plastic cap nails or plastic cap staples. Do **NOT** use nails or staples without caps.

See detailed installation instructions on back of FeltBuster™ High-Traction Synthetic Roofing Felt wrapper.
For technical questions, call 1-800-ROOF-411.



Advantages:

- **Enhanced Walkability** — Special spunbound surface helps provide increased traction vs. traditional asphalt felts
- **Tough Synthetic Construction** — Resists tearing and, unlike asphalt felts, FeltBuster™ High-Traction Synthetic Roofing Felt will not absorb moisture, become brittle in cold weather, or leach oils
- **Easier to Work With** — Super-lightweight, 10 square, 48" (1.23 m) wide roll (vs. typical 36" [914 mm] wide felt rolls)
- **Cooler to Work On** — Medium-gray surface is cooler than typical black asphalt felts
- **Competitively Priced** — with #15 and #30 asphalt felts (per square basis)
- **UV Resistance** — Resists UV degradation for up to 90 days¹
- **Peace of Mind** — Part of the GAF Lifetime Roofing System and covered by up to a Lifetime Ltd. warranty when installed on Lifetime Shingle roofs²

Applicable Standards

Meets or exceeds the physical requirements of ASTM D226 and D4869

Product Specifications (nominal)

Roll Size	One Square = 100 sq. ft. (9.29 m ²) 10 Squares/Roll;* 21 Rolls per Pallet
Roll Coverage	1,000 sq. ft. (92.9 m ²)*
Roll Length	250 ft. (76.2 m)
Roll Width	48 in. (1.23 m)
Approx. Roll Weight	23 lbs (10.4 kg)/Roll

* excludes laps

¹ **NOTE:** Based on standard QUV testing. 90-day UV resistance refers to standardized testing conducted to ensure the product will not physically degrade when exposed to UV. It is **NOT** related to withstanding water, snow, or wind. FeltBuster™ High-Traction Synthetic Roofing Felt is **water resistant**; it is **NOT WATERPROOF. DO NOT USE** FeltBuster™ High-Traction Synthetic Roofing Felt as a temporary roof to protect property or possessions.

² See *GAF Shingle & Accessory Ltd. Warranty* for complete coverage and restrictions. The word "Lifetime" means as long as the original individual owner(s) of a single-family detached residence [or the second owner(s) in certain circumstances] owns the property where the shingles and accessories are installed. For owners/structures not meeting the above criteria, Lifetime coverage is not applicable. Lifetime Ltd. warranty on accessories requires the use of at least three qualifying GAF accessories and the use of Lifetime Shingles.