

# Material Safety Data Sheet

Issuing Date 28-May-2013

Revision Date 10-Jul-2013

Revision Number 2

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** Lead Acid (Non-Spillable) Battery

**Recommended Use** Lead acid battery. Lead Acid (Non-Spillable) Battery.

**Supplier Address**  
Leoch Battery Corp  
19751 Descartes  
unit A  
Foothill Ranch  
California  
92610  
US  
Phone:800-424-9300  
Fax:949-588-5966  
Contact:Paul Yu  
Email:paulyu@leoch.us  
Contact Phone949-588-5853

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

NOTE: Under normal conditions of battery use, internal components will not present a health hazard. The following information is provided for battery acid and lead exposure that may occur during battery production or container breakage or under extreme heat conditions such as fire

In case of rupture:  
Corrosive  
The product causes burns of eyes, skin and mucous membranes

**Appearance** No information available, **Physical State** Solid. **Odor** Odorless  
Black

### Potential Health Effects

**Principle Routes of Exposure** Skin contact.

### Acute Toxicity

**Eyes** Corrosive to the eyes and may cause severe damage including blindness.  
**Skin** Causes burns.  
**Inhalation** Harmful by inhalation. Contact with moist mucous membranes of the respiratory system can cause caustic condition resulting in burns.  
**Ingestion** Harmful if swallowed. Can burn mouth, throat, and stomach.

### Chronic Effects

Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming system and the reproductive system. Avoid repeated exposure.

### Main Symptoms

Severe exposures can lead to shock, circulatory collapse, and death. Lead poisoning is characterized by a metallic taste in the mouth, loss of appetite indigestion, nausea, vomiting, constipation, sleep disturbances and overall weakness

### Aggravated Medical Conditions

None known.

**Environmental Hazard**

See Section 12 for additional Ecological Information.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %
Lead	7439-92-1	60-100
Sulfuric acid	7664-93-9	15-40
ABS resin	9003-56-9	10-30
Tin	7440-31-5	0.1 - 1
Calcium	7440-70-2	0.1 - 1

**4. FIRST AID MEASURES**

<b>General Advice</b>	First aid is upon rupture of sealed battery.
<b>Eye Contact</b>	Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
<b>Skin Contact</b>	Immediate medical attention is required. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
<b>Inhalation</b>	Move to fresh air. Call a physician or Poison Control Center immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
<b>Ingestion</b>	Immediate medical attention is required. Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Remove from exposure, lie down.
<b>Notes to Physician</b>	Treat symptomatically.
<b>Protection of First-aiders</b>	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

**5. FIRE-FIGHTING MEASURES**

<b>Flammable Properties</b>	Not flammable.
<b>Flash Point</b>	Not determined.
<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Uniform Fire Code</b>	• Corrosive: Acid-Liquid
<b>Hazardous Combustion Products</b>	Hazardous metal fumes and oxides.
<b>Explosion Data</b>	
<b>Sensitivity to Mechanical Impact</b>	No.
<b>Sensitivity to Static Discharge</b>	No.
<b>Specific Hazards Arising from the Chemical</b>	The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA**                      **Health Hazard 3**                      **Flammability 0**                      **Stability 2**                      **Physical and Chemical Hazards -**

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Use personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not get in eyes, on skin, or on clothing.
<b>Environmental Precautions</b>	Refer to protective measures listed in Sections 7 and 8.
<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so.
<b>Methods for Cleaning Up</b>	In case of rupture: Use personal protective equipment. Dam up. Soak up with inert absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.
<b>Other Information</b>	Refer to protective measures listed in Sections 7 and 8.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Handle in accordance with good industrial hygiene and safety practice.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lead 7439-92-1	TWA: 0.05 mg/m <sup>3</sup>	TWA: 50 µg/m <sup>3</sup> Action Level: 30 µg/m <sup>3</sup> Poison, See 29 CFR 1910.1025	IDLH: 100 mg/m <sup>3</sup> TWA: 0.050 mg/m <sup>3</sup>
Sulfuric acid 7664-93-9	TWA: 0.2 mg/m <sup>3</sup> thoracic fraction	TWA: 1 mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 15 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
Tin 7440-31-5	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> Sn except oxides (vacated) TWA: 2 mg/m <sup>3</sup>	IDLH: 100 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup>

*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.*

<b>Other Exposure Guidelines</b>	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
<b>Engineering Measures</b>	Showers Eyewash stations Ventilation systems
<b>Personal Protective Equipment</b>	
<b>Eye/Face Protection</b>	Tightly fitting safety goggles.
<b>Skin and Body Protection</b>	Wear protective gloves/clothing.
<b>Respiratory Protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	No information available, Black.	<b>Odor</b>	Odorless.
<b>Odor Threshold</b>	No information available	<b>Physical State</b>	Solid
<b>pH</b>	No information available		
<b>Flash Point</b>	No information available.	<b>Autoignition Temperature</b>	No information available
<b>Decomposition Temperature</b>	No information available	<b>Boiling Point/Range</b>	No information available
<b>Melting Point/Range</b>	No information available		
<b>Flammability Limits in Air</b>	No information available	<b>Explosion Limits</b>	No information available
<b>Water Solubility</b>	Immiscible in water	<b>Solubility</b>	No information available
<b>Evaporation Rate</b>	No information available	<b>Vapor Pressure</b>	No data available
<b>Vapor Density</b>	No data available	<b>Partition Coefficient: n-octanol/water</b>	

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under recommended storage conditions.
<b>Incompatible Products</b>	Incompatible with strong acids and bases. Incompatible with oxidizing agents.
<b>Conditions to Avoid</b>	Exposure to air or moisture over prolonged periods.
<b>Hazardous Decomposition Products</b>	Thermal decomposition can lead to release of toxic/corrosive gases and vapors
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known or supplied information.
<b>Irritation</b>	Causes severe irritation and or burns

### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Sulfuric acid	= 2140 mg/kg ( Rat )	-	= 510 mg/m <sup>3</sup> ( Rat ) 2 h

### Chronic Toxicity

<b>Chronic Toxicity</b>	Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming system and the reproductive system. Avoid repeated exposure.
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lead	A3	Group 2A	Reasonably Anticipated	X
Sulfuric acid	A2	Group 1	Known	X
ABS resin		Group 3		

#### **ACGIH: (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

**NTP: (National Toxicity Program)**

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA: (Occupational Safety & Health Administration)**

X - Present

**Reproductive Toxicity**

Product is or contains a chemical which is a known or suspected reproductive hazard.

**Developmental Toxicity**

Contains ingredients that have suspected developmental hazards. Inorganic lead compounds can cause developmental damage.

**Target Organ Effects**

None known.

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lead		LC50: 0.44 mg/L (96 h semi-static) <i>Cyprinus carpio</i> LC50: 1.17 mg/L (96 h flow-through) <i>Oncorhynchus mykiss</i> LC50: 1.32 mg/L (96 h static) <i>Oncorhynchus mykiss</i>		EC50: 600 µg/L (48 h ) water flea
Sulfuric acid		LC50: > 500 mg/L (96 h static) <i>Brachydanio rerio</i>		EC50: 29 mg/L (24 h ) <i>Daphnia magna</i>

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Should not be released into the environment.

**Contaminated Packaging** Do not re-use empty containers.

**US EPA Waste Number** D002  
D008

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Lead - 7439-92-1	(hazardous constituent - no waste number)	Included in waste streams: F035, F037, F038, F039, K002, K003, K005, K046, K048, K049, K051, K052, K061, K062, K064, K065, K066, K069, K086, K100, K176	= 5.0 mg/L regulatory level	

**California Hazardous Waste Codes** 792

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California EHW	California Carc	California Hazardous Waste	California Waste - Part 2
Lead			Toxic	TCLP (for CA Toxicity): 5.0 mg/L
Sulfuric acid			Toxic Corrosive	
Calcium	Ignitable Reactive			

### 14. TRANSPORT INFORMATION

**Note:** Exempt from hazardous materials regulations per 49CFR173.159(d).

**DOT**  
**Description** NOT REGULATED  
NON-SPILLABLE BATTERY

**TDG**  
**Description** Not regulated  
NON-SPILLABLE BATTERY

**MEX**  
**Description** Not regulated  
NON-SPILLABLE BATTERY

**ICAO**  
**Description** Not regulated  
NON-SPILLABLE BATTERY

**IATA**  
**Description** Not regulated  
NON-SPILLABLE BATTERY

**IMDG/IMO**  
**Description** Not regulated  
NON-SPILLABLE BATTERY

## 15. REGULATORY INFORMATION

### International Inventories

TSCA Complies  
 DSL Not determined

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Lead	7439-92-1	60-100	0.1
Sulfuric acid	7664-93-9	15-40	1.0

#### **SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Lead		X	X	
Sulfuric acid	1000 lb			X

#### **Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Chemical Name	CAS-No	Weight %	HAPS data	VOC Chemicals	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Lead	7439-92-1	60-100				

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Lead	10 lb	
Sulfuric acid	1000 lb	1000 lb

### U.S. State Regulations

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Lead	7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Sulfuric acid	7664-93-9	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Lead	X	X	X	X	X
Tin	X	X	X		
Calcium	X	X	X		
Sulfuric acid	X	X	X	X	X

**International Regulations****Mexico - Grade**

Minimum risk, Grade 0

Chemical Name	Carcinogen Status	Exposure Limits
Lead	A3	Mexico: TWA= 0.15 mg/m <sup>3</sup>
Tin		Mexico: TWA 2 mg/m <sup>3</sup> Mexico: STEL 4 mg/m <sup>3</sup>
Sulfuric acid	A2	Mexico: TWA 1 mg/m <sup>3</sup>

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class**

D2A Very toxic materials

E Corrosive material



Chemical Name	NPRI
Lead	X
Sulfuric acid	X

**Legend**

NPRI - National Pollutant Release Inventory

**16. OTHER INFORMATION**

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 28-May-2013

**Revision Date** 10-Jul-2013

**Revision Note** No information available

**General Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**



