



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 3/30/10

## DAP<sup>®</sup> KWIK SEAL<sup>®</sup> Kitchen and Bath Adhesive Caulk

- Waterproof seal
- Cured caulk is mold and mildew resistant
- Paintable
- Easy water clean-up

**Packaging:** 5.5 fl. oz. (162 mL), 10.1 fl oz. (300 mL) white only  
**Color:** White, Almond  
**UPC Number:** 70798 18001, 70798 18013, 70798 18032

### Company Identification:

**Manufacturer:** DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224  
**Usage Information:** Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"  
**Order Information:** 800-327-3339  
**Fax Number:** 410-534-2650

### Product Description:

**DAP<sup>®</sup> KWIK SEAL<sup>®</sup> Kitchen & Bath Adhesive Caulk** is an easy-to-use, multi-purpose adhesive caulk ideal for caulking and sealing in the bathroom and kitchen. It bonds like a glue and seals like a caulk. It is specially formulated to provide a watertight seal around tubs, sinks, showers and countertops. Cured caulk is mold and mildew resistant. It offers excellent adhesion, flexibility and durability. It tools easily and dries tack free in 15 minutes. Excellent for areas subject to water contact and high humidity. Dried surface cleans easily and is paintable with either latex or oil-based paint. Resists abrasive chemicals. Easy water clean-up.

### Suggested Uses:

*Ideal for Caulking and Sealing:*

- Tubs
- Shower Stalls
- Fixtures
- Sinks
- Countertops
- Repairing loose tiles
- Backsplashes
- Toilets
- Other cracks and joints

*Outstanding Adhesion to:*

- Ceramic Tile
- Porcelain
- Metal
- Plastic Tile
- Plaster
- Drywall
- Glass
- Wood
- Fiberglass

### Performance Characteristics:

- Cured caulk is mold and mildew resistant.
- Easy water clean-up.
- Provides a waterproof seal.
- Does not discolor or yellow.
- Resists cracking, crumbling and shrinking.

### **Surface Preparation & Application:**

1. Surface must be clean, dry and free of all old caulk, dirt, dust and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap if using the tube. Cut nozzle at 45° angle to desired bead size. Load cartridge into caulking gun if using the 10.1 oz cartridge. Joint gap should not exceed 3/8". If joint depth exceeds 3/8", use backer rod material.
3. Fill gap with caulk, pushing caulk ahead of nozzle.
4. For a neat finish, smooth bead of caulk with finishing tool.
5. Clean up excess uncured caulk with a damp cloth before it skins over (15 minutes). Excess cured caulk must be cut or scraped away.
6. Reseal tube/cartridge for future use.

### ***For Best Results:***

- Apply in temperatures above 40°F.
- Not for continuous underwater use. Do not apply product under shower door track or in closed applications.
- Allow caulk to dry at least 2 hours (longer in cool or humid conditions) before painting with latex or oil-based paints.
- Allow to dry and fully cure for at least 36 hours before exposing to water and moisture.
- Store caulk away from extreme heat or cold.

### **Physical & Chemical Characteristics:**

Tooling Time:	10 Minutes
Tack Free Time:	15 Minutes
Paintability:	Yes
Odor:	Very Mild
Consistency:	Smooth and Creamy
Vehicle:	Latex Polymer
Volatile:	Water
Flash Point:	None
Filler:	Calcium Carbonate
Solids:	White/Colors: 68 ± 1% by weight
Weight per Gallon:	11.81 ± .05 lbs.
Temperature Service Range:	-20°F to 150°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles 0°F
Applications:	Interior
Shelf Life:	12 months
Coverage:	5.5 fluid ounces: 30 linear ft. at a 3/16" diameter bead or 2 bathtubs 10.1 fluid ounces: 55 linear ft. at 3/16" diameter bead or 4 bathtubs
MSDS No:	00010009001

### **Clean Up:**

Clean up excess caulk with a damp cloth before it skins over (15 minutes). Dried material must be cut or scraped away.

### **Safety:**

See product label or Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by calling 888-DAP-TIPS or by visiting our website at dap.com.

**Satisfaction Guaranteed:**

If not satisfied with product's performance when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.