



REJUVENATOR™ DECK CLEANER + SEALER

DESCRIPTION AND USES

Rust-Oleum® Rejuvenator™ Deck Cleaner + Sealer is a proprietary formulation designed to remove tough stains from mildew, mold, algae, fungus and moss, and leaves the surface completely clean with waterproofing protection.

It is suitable for use on coated or uncoated decks, porches and docks. It can also be used on concrete patios and walkways. Rejuvenator Deck Cleaner + Sealer is for EXTERIOR USE ONLY.

PRODUCTS

SKU	Description
303569	Rejuvenator 1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

CLEAN – Attach a garden hose to the back of the hose end sprayer with the valve on the sprayer in the 'OFF' position. Turn on the garden hose. Move the valve to the 'CLEAN' position and spray some of the cleaner onto the surface of the deck. Clean the surface using a deck brush to remove any dirt and debris. RINSE – Move the valve to the 'rinse' position to remove any dirt and debris from the deck surface.

PRECAUTIONS & TEMPERATURE SAFEGUARDS

DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS OF APPLICATION. Apply when air and surface temperature is between 45°F (7°C) and 100°F (38°C) for at least 3 hours after application with the relative humidity below 85%.

PRODUCT APPLICATION (cont)

APPLICATION

Shake well before using. Move the valve on the sprayer to 'CLEAN' AND LIGHTLY SPRAY THE ENTIRE SURFACE BEING SURE NOT TO PUDDLE THE SURFACE. Do not rinse off. The product will dry and provide waterproofing protection.

DRY TIMES

Dry times are based on 70°F and 50% relative humidity. Allow the product to dry for 3 hours before light foot traffic.

CLEAN UP

Use mild soap and water.

STORAGE

KEEP FROM FREEZING. CLOSE CONTAINER AFTER EACH USE TO PRESERVE THE PRODUCT.

KEEP OUT OF REACH OF CHILDREN

TECHNICAL DATA

REJUVENATOR™ DECK CLEANER + SEALER

PHYSICAL PROPERTIES

		REJUVENATOR DECK CLEANER + SEALER
Composition		Proprietary Surfactants
Pigment Type		None
Solvents		Water
Weight	Per Gallon	8.28 lbs
	Per Liter	1.00 kg
Solids	By Weight	10.5%
	By Volume	11.4%
Volatile Organic Compounds		Less than 1% by weight
Practical Coverage at Recommended DFT		Approximately 300 sq.ft./quart. One coat is required.
Dry Time at 70°F (21°C) and 50% Relative Humidity		Allow 3 hours before light foot traffic
Shelf Life		3 years
Flash Point		>200°F (93°C)
Storage		KEEP FROM FREEZING
Safety Information		For additional information, see the SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.