

CONCRETE & GARAGE FLOOR PAINT + PRIMER



APPLICATION INSTRUCTIONS FOR RUST-OLEUM® CONCRETE AND GARAGE FLOOR PAINT AND PRIMER

APPLICATION: RUST-OLEUM® CONCRETE AND GARAGE FLOOR PAINT AND PRIMER is ready to use. Do not thin. Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%. Do not paint outdoors if rain is expected within 48 hours. If using more than one gallon, intermix all cans of the same product to ensure color uniformity. Stir thoroughly before applying. Note: Painted floors may be slippery when wet. If desired, **RUST-OLEUM® ANTI-SKID ADDITIVE** (sold separately) may be added to the mixed coating.

Use a brush or edger to trim the perimeter and hard-to-reach areas. Use a long handled roller and a high-quality, 3/8" nap roller cover to apply an even coat of **RUST-OLEUM® CONCRETE AND GARAGE FLOOR PAINT AND PRIMER** onto the surface. Apply in 4'x 4' sections, and maintain a wet edge to prevent lap marks and gloss differences. Continue applying in 4'x 4' sections until complete. Only one coat is necessary. If a second coat is desired, wait 24 hours before applying the second coat in a direction perpendicular to the first. Occasional touch-up may be necessary for areas subject to heavy vehicle traffic.

RUST-OLEUM® DECORATIVE COLOR CHIPS (sold separately) can be added for an upgraded appearance.

Chips should be applied in 4x4 sections while the coating is wet.