

ADVANGED STONE

Sand Stabilizer and Sealer for Interlocking Pavers and Bricks

One Step

Easy to Apply

Low Sheen



LOCKS SAND BETWEEN JOINTS AND SEALS IN ONE STEP!

- Resists Oil, Grease and Rust
- Efflorescence Resistant
- Resists Weeds
 - Breathable
- Qualifies for LEED points



Professional Results...GUARANTEED!

1-800-486-1414



ONE STEP PAVER SEALER

PRODUCT DESCRIPTION

The ideal one step, easy to apply, product for sealing interlocking concrete pavers and stabilizing joint sand by locking it in place. This state of the art formula offers exceptional stain resistance (even against oil and grease), resists color fading, efflorescence, weeds and mildew growth on the surface. This clear acrylic, water based sealer penetrates the surface providing long-lasting protection and beauty. This unique formula, makes it easy to clean, maintain and even reapply the sealer to refresh the surface as needed.

SPECIAL FEATURES

- Resists oil, grease and rust stains
- Locks sand between paver joints
- Reduces efflorescence and freeze thaw effects
- Cleans up with water
- Non-flammable and no harmful vapors
- Prevents weed growth
- Low Sheen

LIMITATIONS

Apply in temperatures between 45° and 90° F. Air and surface temperature should be above 450 F for 24 hours before and after sealing. Clean up applicators with water immediately after use. Do not apply this sealer to areas where sealer will be immersed such as fountains, pools or below grade areas. Do not use on porcelain, polished stone, granite or marble.

SURFACE PREPARATION

Prior to the application of Glaze 'N Seal products, surface must be thoroughly clean and dry. Remove all dirt, oil, grease, paint, efflorescence and surface sealers. General cleaning may be done using Glaze 'N Seal Heavy Duty Cleaner for Concrete and Masonry. For efflorescence stains use Glaze 'N Seal Efflorescence Remover. When acid has been used for any reason, surface must be neutralized. We recommend Glaze 'N Seal Neutralizing Rinse. Read product container for specific instructions and cautions with any cleaner. Never mix cleaners. Allow at least 24 hours of drying time before sealing (48 hours if power washing has been done or if temperature is cool). New concrete pavers should cure 14 days or more before sealing. Applying sealer to a damp or incompletely cured surface may cause a hazy appearance or loss of adhesion.

After tamping down the joint sand and sweeping the application area clean be sure the sand is at least 1/8 inch below the surface of the pavers. The sand should be dry to its full depth before sealing for best results.

Note: Before applying Glaze 'N Seal products to the entire

surface, test several small areas to verify the product's appearance, penetration and protective ability.

APPLICATION PROCEDURE

Use garden-type sprayer, low pressure airless sprayer, natural bristle brush, short nap roller or squeegee for application. Apply one coat in liberal saturating manner so that joints are saturated with **PAVER SEALER**. Ensure that all joints are flooded to maximize sealer soaking into the dry sand. Roll back or squeegee any excess product to avoid puddling on the surface. Allow additional drying time in moist, cool climates. An optional second coat may be applied after two hours if desired to increase protection and gloss. For added slip resistance **Glaze'** N Seal Grip 'N Seal Slip Resistance Additive may be added to the second coat of sealer.

COVERAGE

75 to 150 square feet per gallon depending on porosity of surface and method of application.

WARRANTY

Glaze 'N Seal Product liability, either expressed or implied, is limited solely to the replacement of this product when proven to be defective and does not include any labor costs or conse-quential damages. It is the user's responsibility to determine the safety, toxicity and suitability of this product.

SAFETY INFORMATION

CAUTION, Liquid contact with eyes and skin causes irritation. Do not ingest. Wash hands thoroughly after use.

FIRST AID: Should eye contact occur, flush with plenty of water for 15 minutes. If irritation persists get medical attention. For skin contact flush skin with pleanty of soap and water. If irritation persists get medical attention. If swallowed get medical attention immediately. Do not induce vomiting.

KEEP OUT OF REACH OF CHILDREN.

VOC <100 g/l.

ADVANCED STONE CARE PRODUCT LINE

Paver Sealer is part of Glaze 'N Seal's Advanced Stone Care line of products to protect, maintain, and restore marble, granite, limestone and other fine stone. This "state-of-the-art" product line includes sealers, polishes, cleaners and restoration products. All products are effective, safe to use and easy to use.

For additional information, contact your Glaze 'N Seal dealer or contact Glaze 'N Seal directly.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • www.glaze-n-seal.com