



# OIL-LATEX REDWOOD STAIN

NO. 9



## PRODUCT INFORMATION

BEHR® Oil-Latex Redwood Stain produces a deep, redwood tone, color stain that protects exterior wood surfaces. The unique formula penetrates wood surfaces and remains flexible to resist cracking, flaking and peeling on properly prepared surfaces.

## RECOMMENDED USES:

Recommended for properly prepared new to moderately weathered, unsealed exterior wood surfaces such as:

- Wood
- Plywood

- Pressured Treated Lumber

Do not use on horizontal surfaces subject to foot traffic.

## PRODUCT SPECIFICATIONS:

### Tint Bases/Max Tint Load:

No. 9 128 oz.

**Resin Type:** Oil-Latex

**Weight per Gallon:** 9.7 lbs

**% Solids by Volume:** 21.6%

**% Solids by Weight:** 32.6%

**VOC:** <100 g/L

**Flash Point:** N/A

**Viscosity:** 55-60 KU

### Recommended Film Thickness:

Wet: 7.8 Dry: 1.7 mils @ 200 Sq. Ft./Gal.

Wet: 3.9 Dry: 0.9 mils @ 400 Sq. Ft./Gal.

**Coverage:** 200-400 Sq. Ft./Gal. depending on application method and substrate porosity.

## APPLICATION:

**Brush:** Natural Bristle

**Roller:** 3/8"-3/4" nap

**Pad Applicator**

**Airless Spray:** At packaged consistency

**Tip:** .015- .019"

**Filter:** 60 mesh

**Dry Time:** @ 77° & 50% RH

**To Touch:** 1 hour

**To Recoat:** 4 hours

- Follow spraying immediately with a pad, back brushing, or back rolling for a uniform appearance.
- Maintain a wet edge when applying.

## SURFACE PREPARATION:

### The following steps and products are recommended for best results:

If you use a product such as BEHR PREMIUM® Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new weathered wood, then you must use a product such as BEHR PREMIUM® All-In-One Wood Cleaner No. 63 to clean, brighten & neutralize wood. If you do not use a product such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64, then use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Lightly sand any remaining wood fibers/fuzz.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

### COMPLIES WITH THE BELOW AS OF 9/1/2014

SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES	LEED v.3 (2009) <sup>†</sup>	YES

## CAUTIONS/LIMITATIONS:

- Protect from freezing
- Do not use if rain is expected within 24 hours
- DO NOT THIN PRODUCT
- Avoid applying stain in direct sunlight or hot surfaces
- Test product for color on a small hidden area before proceeding
- Over application of stain will lead to surface failure including peeling & cracking
- Shelf life under normal conditions is two years (unopened containers)
- Temperature Range: 40-90°F (4.5-32°C).

## GENERAL INFORMATION:



**Warning!** Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid: If in eyes:** Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.