

Stone Arch Fireplace

Setup Instructions Stone-Arch-FP-1224-K



Congratulations on your purchase of a new outdoor gas fireplace!

These instructions will help you get your new fireplace set up in no time. Be sure to thoroughly read your gas burner instruction manual for important safety information and special considerations.

Required Tools:

- Razor Knife
 - · For cutting packaging
- Leather work gloves
 - To protect hands from rough and sharp edges of inner steel framing
- ➢ IT IS RECOMMENDED THAT A MINIMUM OF TWO PEOPLE ASSEMBLE THIS FIREPLACE
- It is also recommended that a minimum of two people use the fireplace together for full enjoyment.

<u>Unwrapping your Fireplace</u>

WARNING!

The supercast top of this fireplace is not attached. Do not slide or move the unit until this has been removed.



Using a razor knife, carefully cut plastic covering fireplace, taking care to avoid cutting or scraping the unit inside.



With a minimum of two people, carefully remove cast concrete top from packaging and set in a safe place until the fireplace is in its desired location.

<u>Locating your Fireplace</u>



No hearth extensions are needed for this fireplace.



Position fireplace in desired location and ensure that clearances are met.


Clearances to combustibles are as follows-

Front: 24" to front opening.

Sides and back: Zero clearance. (Plan for space on the right side to access propane tank and control panel)



With a minimum of two people, set the supercast top on the fireplace. The 2" overhang should be on the <u>FRONT</u> side of the fireplace (stone texture side up)



<u>Final Steps</u>

- Cut open bags of glass beads and scatter evenly on burner surface. **DO NOT** burn without beads or similar material covering burner pan.
- Unscrew the sparker button (cap unscrews by turning counter-clockwise) and insert a single AAA battery with the positive (+) side facing outward. Replace cap
- The Stone Arch is supplied to you set up for liquid propane but can easily be converted to natural gas following the instructions supplied in your crystal fire owner's manual (supplied separate from this user guide)
- Space is provided to position a 20 lb. propane tank inside the cabinet. After installing the tank, the fireplace is ready for use.

As with all gas appliances, have a qualified licensed professional check all gas connections for leaks.

Operation

- Ensure that all gas valves (control panel and propane or natural gas source/tank) are in the OFF position.
- To light fireplace, turn on tank or supply valve and press the sparker button. You should see and hear a constant spark at the electrode on your burner.
- Continue to press sparker button while turning the knob on your control panel to the on position. Once flame is lit, release the sparker button.
- If the burner does not light within 4 seconds, turn off the gas for 5 minutes to allow raw gas to dissipate. Repeat lighting procedure.
 - (OPTIONAL) Install Logs and accessories as detailed in the provided instructions for those products.

IMPORTANT

Please consult your Crystal Fire instruction manual for detailed instructions and important information related to hooking up your CF-1224 burner, including safety information, proper tightening of connections with two wrenches and full burner setup and lighting instructions.

DO NOT ATTEMPT TO
INSTALL CF-1224 BURNER
WITHOUT FIRST
CONSULTING THE
MANUAL. IF YOU ARE
UNSURE OF HOW TO
COMPLETE THE STEPS
OUTLINED, CONSULT A
QUALIFIED TECHNICIAN

WARNING

After consulting the manual and following instructions, remember; before operating, all gas connections must be fully checked for leaks

Warranty: Your outdoor fireplace is covered under a 1-year manufacturer's warranty. Please visit http://www.outdoorrooms.com/warranty-form to register your product.



© 2013	The Outdoor GreatRoom Company		
		8 P a	g e