

# **HIGHBRIDGETM**

#### **Features**

- Cast iron with Safeguard® finish
- Drop-in with three-sided flange
- Available with or without an enameled apron
- 60" (1524 mm) x 32" (813 mm) x 17-1/2" (445 mm)


## **Codes/Standards Applicable**

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.19.1/CSA B45.2







### Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

#### **Accessories**

- CP: Polished Chrome
- 0: White
- Other: Refer to Price Book for additional colors/finishes

## **Specified Model**

Model	Description	Colors/Finishes	
K-877	Bath – left drain	□ 0	☐ Other
K-877-S	Bath – for use with custom storage, left drain	□ 0	☐ Other
K-878	Bath – right drain (shown)	□ 0	☐ Other
K-878-S	Bath – for use with custom storage, right drain	□ 0	☐ Other

Required Accessories						
K-7214	Clearflo cable bath drain, less PVC tubing	□ CP	☐ Other			
K-7261	Fitting/pipe kit			□ NA		

## **Product Specification**

The bath shall be made of cast iron with Safeguard $_{\odot}$  finish. Bath shall be 60" (1524 mm) in length, 32" (813 mm) in width, and 17-1/2" (445 mm) in height. Bath shall be drop-in with three-sided flange. Bath shall be for alcove installations. Bath shall be available with or without an enameled apron. Bath shall be Kohler Model K-\_\_\_\_\_.

# **HIGHBRIDGETM**

### **Technical Information**

Fixture*:				
Bathing well:				
Basin area, bottom	43-7/8" (1114 mm) x 20-15/16" (532 mm)			
Basin area, top	53-3/16" (1351 mm) x 23-5/16" (592 mm)			
Weight	275 lbs (124.7 kg)			
To overflow:				
Water depth	12-13/16" (325 mm)			
Capacity	49.5 gal (187.4 L)			
* Approximate measurements for comparison only.				

### **Installation Notes**

Install this product according to the installation guide.

Floor support under bath must provide for minimum of 54 lbs/square foot (262 kg/square meter) loading.

Will comply with **ADA** when installed per Section 607 Bathtubs of the Act.

Will comply with **CSA B651** when installed per Clause 4.4.7 of the standard.

Will comply with **OBC** when installed per Clause 3.8.3.13.

