

## MATERIAL SAFETY DATA SHEET

MSDS 0495

 =====  
 Section 1 -- PRODUCT AND COMPANY IDENTIFICATION  
 -----

		HMIS CODES	
PRODUCT NAME		Health	1
Nokorode Regular Paste Flux		Flammability	1
		Reactivity	0
PRODUCT CODES		PPI	B
14000, 14010, 14020, 14030			
CHEMICAL FAMILY:			
Organic/Inorganic			
USE			
Soldering Flux			
MANUFACTURER'S NAME		EMERGENCY TELEPHONE NO.	
The RectorSeal Corporation		Chemtrec 24 Hours	
2601 Spenwick Drive		(800) 424-9300	
Houston, Texas 77055 USA			
VALIDATION DATE		TECHNICAL SERVICE TELEPHONE NO.	
February 16, 2006		(800) 231-3345	
REVISION DATE			
February 16, 2006			

 =====  
 Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS  
 -----

% by WT	CAS No.	INGREDIENT	UNITS
10-25	7646-85-7	Zinc Chloride	
		ACGIH TLV	1 mg/m3
		OSHA PEL	1 mg/m3
10-25	12125-02-9	Ammonium Chloride	
		ACGIH TLV	10 mg/m3
		OSHA PEL	10 mg/m3
70-90	8009-03-8	Petrolatum	
		ACGIH TLV	N/D
		OSHA PEL	N/D

 =====  
 Section 3 -- HAZARDS IDENTIFICATION  
 -----

## SUMMARY OF ACUTE HAZARDS

Irritation to respiratory system from fumes evolved during soldering.  
 Eye contact may cause intense irritation and injury.

## ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

## INHALATION

Irritation to respiratory system from fumes evolved during soldering.

## EYE CONTACT

Contact may cause intense irritation and injury.

## SKIN CONTACT

May cause skin irritation.

## INGESTION

Nausea, vomiting, irritation to digestive system.

## SUMMARY OF CHRONIC HAZARDS

Short term effects to liver and kidneys can occur. Chemical irritation from continued skin contact can occur. Continuous industrial use in small unventilated areas may result in sufficient inhalation of solder and flux

fumes to cause lung damage and irritation of respiratory tract.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

Section 4 -- FIRST AID MEASURES

- If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
- If on SKIN: Immediately wash with soap and water. Remove and wash any contaminated clothing.
- If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.
- If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
>400 F (204 C) SETA CC	N/D	N/D

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and other protective clothing. Hazardous decomposition products possible (see Section 10). May release ZnO and HCl fumes.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heat may build up pressure and rupture closed containers.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Store flux at ambient conditions. Wash thoroughly after handling to remove all residue.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: N/A

MECHANICAL (GENERAL): Acceptable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)  
 OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.  
 WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

=====  
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
 -----

BOILING POINT: N/A  
 SPECIFIC GRAVITY (H2O = 1): 1.06  
 VAPOR PRESSURE (mm Hg): < 0.01 @ 68 F (20 C)  
 MELTING POINT: 120-150 F (52-66 C)  
 VAPOR DENSITY (AIR = 1): N/A  
 EVAPORATION RATE (ETHYL ACETATE = 1): N/A  
 APPEARANCE/ODOR: Tan / Petroleum Odor  
 SOLUBILITY IN WATER: Insoluble

VOLATILE ORGANIC COMPOUNDS (VOC) Content  
 (Theoretical Percentage By Weight): 0% or (0 g/L)

=====  
 Section 10 -- STABILITY AND REACTIVITY  
 -----

STABILITY: Stable  
 CONDITIONS TO AVOID: None  
 INCOMPATIBILITY (MATERIALS TO AVOID): None known  
 HAZARDOUS DECOMPOSITION PRODUCTS: Toxic fumes of zinc, chlorine, and HCL may be evolved during soldering.  
 HAZARDOUS POLYMERIZATION: Will not occur.

=====  
 Section 11 -- TOXICOLOGY INFORMATION  
 -----

CHRONIC HEALTH HAZARDS  
 No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

-----  
 TOXICOLOGY DATA  
 Ingredient Name  
 -----

Zinc Chloride  
                   Oral-Rat LD50:350 mg/kg  
                   Inhalation-Rat LCLo:1960 mg/m3/10M  
 Ammonium Chloride  
                   Oral-Rat LD50:1650 mg/kg  
                   Inhalation-Rat LC50:N/D  
 Petrolatum  
                   Oral-Rat LD50:N/D  
                   Inhalation-Rat LC50:N/D

=====  
 Section 12 -- Ecological Information  
 -----

-----  
 ECOLOGICAL DATA  
 Ingredient Name  
 -----

Zinc Chloride  
                   Food Chain Concentration Potential           None  
                   WATERFOWL TOXICITY                               N/A  
                   BOD   None  
                   AQUATIC TOXICITY: 7.2 ppm/96 hr/medium bluegill/TLm

Ammonium Chloride

Food Chain Concentration Potential	None
WATERFOWL TOXICITY	N/A
BOD	N/A
AQUATIC TOXICITY:	6 ppm/96 hr/sunfish TLm

Petrolatum

Food Chain Concentration Potential	N/D
WATERFOWL TOXICITY	N/D
BOD	N/D
AQUATIC TOXICITY:	N/D

=====  
Section 13 -- DISPOSAL CONSIDERATIONS  
-----

Waste Classification: Non-regulated solid waste  
Disposal Method: Approved landfill  
Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

=====  
Section 14 -- TRANSPORTATION INFORMATION  
-----

DOT: Non-Regulated  
OCEAN (IMDG): Non-Regulated  
AIR (IATA): Non-Regulated  
WHMIS (CANADA): Non-Regulated

=====  
Section 15 -- REGULATORY INFORMATION  
-----

REGULATORY DATA

Ingredient Name

Zinc Chloride

SARA 313	Yes
TSCA Inventory	Yes
CERCLA RQ	1000 lb.
RCRA Code	N/A

Ammonium Chloride

SARA 313	No
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

Petrolatum

SARA 313	No
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

=====  
Section 16 -- OTHER INFORMATION  
-----

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001