



## Urethane Alkyd Semi-Gloss Enamel

NO. 3900 White  
NO. 3930 Deep Base

- Professional Quality Interior/Exterior Semi-Gloss Finish
- Excellent Flow & Leveling
- Less Odor than Oil-base Paint
- Easy Water Clean-up
- Durable Hard Finish
- Easy Stain Removal
- Mildew Resistant Finish



**2 Coats Recommended**  
for Optimal Durability



**Spread Rate:**  
Rough 350-400 Sq. Ft.  
Smooth 500-550 Sq. Ft.



**Dry Time:**  
2-4 Hr. Dry to Touch  
4-8 Hr. Recoat



**Soap & Water**  
Clean-Up

**WHITE BASE: READY TO USE OR ADD TINTING COLORANTS.**

**MEDIUM & DEEP BASE: DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.**

### WHERE TO USE

Properly prepared Interior/Exterior metal & wood surfaces. Ideal for Doors, Trim, Molding, Cabinetry, Plaster, Masonry, Cinder Block, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Wrought Iron.

**Do not use on horizontal surfaces subject to foot traffic.**

### PREPARATION†

**(Proper surface preparation is required.)** Allow new stucco, plaster and masonry to cure for 30 days. For interior and exterior surfaces, remove dirt, oil and grease stains with a Concrete & Masonry Degreaser & Cleaner. Remove mildew stains with a mildew stain removing product. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, power wash to remove chalk. Etch galvanized metal with a Concrete & Masonry Cleaner & Etcher. Follow all label instructions.

### PRIME

**Interior:** On interior surfaces with heavy stains, galvanized metal or wrought iron, use a product such as BEHR PREMIUM PLUS® NO. 75 Stain-Blocking Primer & Sealer. **Exterior:** On exterior surfaces with heavy stains, wood or metal, use a product such as BEHR PREMIUM PLUS NO. 436 Multi-Surface Primer & Sealer. Follow all label instructions.

### APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application and drying process. Certain colors may require 2 or more coats to achieve complete hide and coverage. Use product when air and surface

temperatures are 50-90°F (10-32°C). Apply a thin coat using a high quality synthetic brush, 1/4"-3/8" nap roller or an airless sprayer (.013"-.017" spray tip). NOTE: If touch-up is necessary, same application method is recommended.

### DRY TIME

Longer dry time required in cooler temperatures and higher humidity. Wait at least 7 days before rinsing or cleaning the surface with a mild, non-abrasive detergent.

### DISPOSAL

Properly dispose of all soiled rags. For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

#### \*LIMITED WARRANTY

For one year from the date of purchase, Behr Process Corporation warrants to the original consumer purchaser, (1) that the product meets Behr Process Corporation's manufacturing specifications, and (2) the performance of this product when applied according to the label instructions and specifications. If this product is found not to perform as specified on the label within one year from the date of purchase, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. To the extent permitted by applicable law, any implied warranties including the implied warranties of merchantability and of fitness for a particular purpose, are limited to the duration of this express warranty. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. **Note to residents of the State of New Jersey:** The provisions of this warranty, including its limitations, are intended to apply to the fullest extent permitted by the laws of the State of New Jersey. To obtain warranty service, call 1-800-854-0133. Behr Process Corporation reserves the right to inspect any and all application of the product prior to processing your claim made under this warranty.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**WARNING** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CAUTION IRRITANT** MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**



©2019 Behr Process Corporation  
Santa Ana, CA 92705 U.S.A. • [behr.com](http://behr.com)  
V.O.C. <50 g/L • REV. 11/18