

# SPEAKMAN® S-9010-CA-E

## Vandal-Resistant Sensorflo® Faucet

### FEATURES:

- Vandal-resistant and Easy Maintenance
- Components housed above counter
- Integral hot and cold mixing valves
- Hot and cold check valves and filters
- Pre-assembled
- All metal housing
- Water conserving vandal-resistant flow control reduces flow to 0.5 gpm (1.89 L/min).
- 60 second flow time out feature
- Lead free brass construction.

### COMPLIANCE:

- ASME A112.18.1/CSA B125.1 certified
- NSF 61 certified
- NSF 372 certified

### FINISH:



PC

### ADD-ONS:

- 0.5 gpm Boca spray outlet & 1.5 gpm laminar flow outlet kit  A-BOLF
- Two (2) stainless steel flexible supply hoses to supply stops  A-HS
- One (1) stainless steel hose for tempered water systems  A-HTS
- Under counter thermostatic mixing valve  A-TMV
- Vandal-resistant screws for removable cover and custom wrench  A-VRS
- 1.2 gpm laminar flow outlet  A-ELF
- 1.2 gpm aerator  A-EA12

### WARRANTY:

- 5 Year Limited



**DIMENSIONS:** NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.  
 2. Inlet is 3/8" compression with male threads. Position faucet as close to the edge of the sink as possible.

