



RAM BOARD - CORPORATE
 716 S. FLOWER ST.
 BURBANK, CA 91502
 818-848-0400 ph
 818-848-0099 fax

WWW.RAMBOARD.COM

Ram Board Grade Specification

(Contractor Grade - Flex-Fiber™ reinforced)

Date generated: 2/14/2006

Grade: 046100-rb
Ram Board - Contractor grade - Flex-Fiber™ reinforced

Grade Specification Created on: 12/12/2003

Specification Last Revised on: 12/12/2003

(Grade Specifications applicable to Ram Board at time of manufacturing.)

<i>Characteristics</i>	<i>Upper Specification</i>	<i>Standard</i>	<i>Lower Specification</i>
Caliper	0.0483	0.0460	0.0437
Width(in.)	n/a	38"	n/a
Length(ft.)	n/a	100'	n/a
Unit Weight(1 roll)	50.4 lbs.	48 lbs.	45.6 lbs.
Basis Weight	n/a	138.00	n/a
Moisture (A.D.)	-	confidential	-
Mullen Plybond (Calc.)	n/a	166.8	155.2
Caliper (Metric)	1,226.80	1,168.40	1,110.00
Basis Weight (Metric)	n/a	673.70	n/a
Width(cm)	n/a	96.52cm	n/a
Length(m)	n/a	30.48m	n/a
Component formula %'s	-	confidential	-

Raw Materials: Up to 100% recyclable fibers - reinforcers (recycled OCC, ply fibers, tube scrap and mixed fiber waste) formula percentages of each component: Confidential
 Flex-Fiber™ strengthening agents

Approvals: Quality Manager - Board Division: Ram Board date: 06/09/2005

Thank you for doing business with Ram Board. This Grade Specification grid has been generated by our manufacturing quality division. If you would like to review any portion of this product information please contact Ram Board at 818-848-0400.