



## Alkyd Satin Enamel

- Professional Quality Interior/Exterior Semi-Gloss Finish
- Excellent Flow & Leveling
- Less Odor than Oil-base Paint
- Easy Water Clean-up
- Durable Hard Finish
- Easy Stain Removal
- Mildew Resistant Finish

NO. 7900 White  
NO. 7930 Deep Base



**2 Coats Recommended**  
for Optimal Durability



**Spread Rate:**  
Rough 350-400 Sq. Ft.  
Smooth 500-550 Sq. Ft.



**Dry Time:**  
2-4 Hr. Dry to Touch  
4-8 Hr. Recoat



**Soap & Water**  
Clean-Up

**WHITE BASE: READY TO USE OR ADD TINTING COLORANTS.**

**MEDIUM & DEEP BASE: DO NOT USE WITHOUT THE ADDITION OF TINTING COLORANTS.**

### WHERE TO USE

Properly prepared Interior/Exterior metal & wood surfaces. Ideal for Doors, Trim, Molding, Cabinetry, Plaster, Masonry, Cinder Block, Well-bonded Wallpaper, Brick, Stucco, Aluminum and Wrought Iron.

**Do not use on horizontal surfaces subject to foot traffic.**

### PREPARATION†

**(Proper surface preparation is required.)** Allow new stucco, plaster and masonry to cure for 30 days. For interior and exterior surfaces, remove dirt, oil and grease stains with a Concrete & Masonry Degreaser & Cleaner. Remove mildew stains with a mildew stain removing product. Remove all loose and peeling paint; scuff sand glossy surfaces; caulk; repair imperfections and sand smooth. For exterior surfaces, power wash to remove chalk. Etch galvanized metal with a Cleaner & Etcher. Follow all label instructions.

### PRIME

**Interior:** On interior surfaces with heavy stains, galvanized metal or wrought iron, use a product such as BEHR PREMIUM PLUS® NO. 75 Stain-Blocking Primer & Sealer. **Exterior:** On exterior surfaces with heavy stains, wood or metal, use a product such as BEHR PREMIUM PLUS NO. 436 Multi-Surface Primer & Sealer. Follow all label instructions.

### APPLICATION

DO NOT THIN. Stir before and during application. When working with more than one can of the same product, intermix to ensure color uniformity. Use adequate ventilation during application and drying process. Certain colors may require 2 or more coats to achieve complete hide and coverage. Use product when air and surface

temperatures are 50-90°F (10-32°C). Apply a thin coat using a high quality synthetic brush, 1/4"-3/8" nap roller or an airless sprayer (.013"-.017" spray tip 60 mesh filter). NOTE: If touch-up is necessary, same application method is recommended.

### DRY TIME

Longer dry time required in cooler temperatures and higher humidity. Wait at least 7 days before rinsing or cleaning the surface with a mild, non-abrasive detergent.

### DISPOSAL

Properly dispose of all soiled rags. For disposal of empty containers and unused product, contact your household refuse collection service.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**CAUTION IRRITANT HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

#### \*LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product does not meet these specifications, Behr Process Corporation will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. **This guarantee excludes (1) labor and costs of labor for application or removal of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

**BEHR**  
A Masco Company

©2017 Behr Process Corporation  
Santa Ana, CA 92704 U.S.A. • [behr.com](http://behr.com)  
V.O.C. <50 g/L • REV. 1/17