



USE **BEIGE** PUTTY ONLY FOR THESE FORMULAS

1	Putty Only	
2	6 C, 1A	2 taps from bowl into 2 lines putty
3	4 A, 2 B, 8 C	6 taps from bowl into 2 lines putty
4	8 A, 2 B, 3 C	2 taps from bowl into 2 lines putty
5	1 C	Add drop to 2 lines putty
6	6 C	Add drops to 2 lines putty
7	10 C	Add drops to 2 lines putty
8	1 A, 10 C	Add drops to 2 lines putty
9	1 A, 1 C	Add drops to 2 lines putty
10	1 A, 2 C	Add drops to 2 lines putty
11	10 A, 10 C	21 taps from bowl into 2 lines putty
12	3 A, 6 C	Add drops to 2 lines putty
13	10 A, 1 B, 1 C	5 taps from bowl into 2 lines putty
14	6 A, 10 C	Add drops to 2 lines putty
15	6 A, 4 C	Add drops to 2 lines putty
16	2 A	Add drops to 2 lines putty
17	10 A	Add drops to 2 lines putty
18	3 A, 3 C	Add drops to 2 lines putty
19	8 A, 2 B, 3 C	4 taps from bowl into 2 lines putty
20	1 B	Add drop to 2 lines putty
21	2 B	Add drops to 2 lines putty
22	6 B	Add drops to 2 lines putty

◀ Wood Formulas  
For matching  
Maple, Oak, Cherry,  
Hickory,  
Walnut, Mahogany,  
and more

## HINTS & TIPS

- Putty will darken greatly as it dries.
- To save time, pre-fill deep gouges with untinted putty and let dry before topping off with final matching color.
- Save all putty mixes (including tests) under plastic wrap or on cards for 2nd application, marbling tests, etc.
- For very fine repairs, trim brush to make it smaller before applying lacquer.
- To achieve very light colors, add a small amount of the putty/tint mixture to some fresh putty until the desired lightness is achieved.
- To slightly alter colors, add tint to some fresh putty first, then add that to your existing mixture.
- For minor scratches, try our ScratchAway concealer or our ScratchCure Repair Pens.
- Always test graining on a scrap piece of putty.
- Put some variations of your mix on cards or post-its, let dry, then hold against your needed repair areas. Save scraps to test graining.
- For a more realistic repair, match the background color (usually much lighter) first, then add darker foreground graining or marbling.
- Final lacquer application can darken some formulas.

Refer to formula charts for which method to use.

### METHOD A: MIX IN BOWL



1) Squeeze required amount of putty onto mixing board



2) Drop tints into mixing bowl



3) Mix tints well



4) Dip mixing stick into the bowl and tap onto board

### METHOD B: DROPS INTO PUTTY



Drop tints directly into putty

### MIX & APPLY



BLEND WELL



APPLY

ONE UNIT OF MEASURE  
3/16-in W x 2-1/2-in L

**CAUTION: EYE IRRITANT** Read instructions carefully

HEALTH AND SAFETY: KEEP OUT OF REACH OF CHILDREN

- Irritating to eye and skin. In case of contact with skin, wash immediately with soap and water. In case of contact with eyes, rinse immediately with plenty of clean, fresh water.
- If swallowed, rinse mouth and throat with cold water. Immediately seek professional medical advice. Take this label with you.

DO NOT INDUCE VOMITING

# CAL FLOR

## HARD SURFACE REPAIR KIT



For ceramic tile, stone, vinyl, laminate, wood, flooring, furniture, concrete, and more!



### USE **BEIGE** PUTTY ONLY FOR THESE FORMULAS

1	20 White	Add drops to 1 line putty
2	5 White	Add drops to 1 line putty
3	1 C 10 White	Add drops to 1 line putty
4	2 A, 2 C 5 White	2 taps from bowl into 2 lines putty
5	2 A, 18 C 4 White 1 Black	3 taps from bowl into 2 lines putty
6	10 C	Add drops to 2 lines putty
7	1 A 10 White	Add drops to 1 line putty
8	1 A, 2 C 20 White	Add drops to 1 line putty
9	6 A, 1 C 4 White	2 taps from bowl into 2 lines putty
10	2 A, 1 C 4 White	Add drops to 1 line putty
11	3 A, 1 Red 10 White 1 C, 1 Yellow	Add drops to 1 line putty
12	1 A, 1 C	Add drops to 2 lines putty
13	3 A, 6 C	Add drops to 2 lines putty
14	2 A	Add drops to 2 lines putty
15	3 A, 10 C 1 Black 12 White	18 taps from bowl into 2 lines putty
16	6 A, 12 C 1 Black 4 White	Add drops to 2 lines putty
17	5 A, 1 Black 10 White	Add drops to 2 lines putty
18	10 A, 1 Blue 5 Red 5 White	Add drops to 1 line putty
19	1 A, 1 Red 1 Yellow 1 Green	Add drops to 1 line putty
20	1 A, 1 Black 10 White	4 taps from bowl into 1 line putty
21	1 Black 10 White	3 taps from bowl into 1 line putty
22	1 Black 10 White 1 Green	4 taps from bowl into 1 line putty
23	1 Black 10 White 1 Green	15 taps from bowl into 1 line putty
24	2 Black 20 White 1 Blue	Add drops to 1 line putty
25	1 Black 10 White	10 taps into 1 line putty
26	1 Black 20 White	Add drops to 2 lines putty
27	1 Black 5 White	Add drops to 1 line putty
28	5 Black	Add drops to 1 line putty

### Vinyl Formulas For All Vinyl Looks! Lvt • Stone • Wood Slate • Ceramic

### CREATING GRAINING OR MARBLING EFFECTS

After repair is complete - and before applying lacquer - add your graining or marbling:

- Mix tints in the bowl to closely match the graining or marbling. It's better to start lighter than darker.
- Add the white tint or water to reduce the strength of the color, if needed.
- Place 3 drops of the lacquer onto the mixing board surface.
- Pull the cotton away from one end of the swab, creating a fine strand, like a fine paint brush.
- Lightly dip the cotton strand in the tint bowl, being careful not to dip the whole swab.
- Draw the strand once or twice through the lacquer on the mixing board.
- Lightly create graining or marbling with the fine strands over the repaired area.
- Allow to dry and apply a coat of clear lacquer over final repair.

### INSTRUCTIONS

#### IMPORTANT: The putty mixture dries much darker.

When mixing, test a small amount of mixed putty on a scrap of cardboard, or on an inconspicuous area of floor before applying to repair area. Use a hair dryer to allow quick color testing and speed drying of applications. Mixture might need adjusting to ensure a good color match.

Hint: Cover mixture with plastic to preserve for a second application or for future use.

#### PREPARATION

All surfaces should be clean and dry. Shake all pigment bottles thoroughly before and during use.

#### APPLICATION

1. Choose a color from the formula chart found inside this package that closest matches the floor.

- It helps to match the floor's background color first, then use graining (described on facing page) to apply the foreground colors and pattern.

Follow directions for the Mixing Method which applies to your formula:

- Method A:** add the required amount of tint drops into the bowl and mix thoroughly with the stick. Dip stick in bowl and apply mix to mixing board with a sharp tap - see photograph 4).

- Method B:** add tint drops directly to the putty.

2. Measure the required amount of putty onto the mixing board by using the reference lines, then add the required tint to putty and mix until the putty is uniform in color.

3. Apply mixed putty to floor with a flat plastic spatula, slightly overfilling the area of repair. Scrape off any surrounding excess with spatula. Allow to dry.

4. When the mixture is freshly dry, gently rub away the excess of the surrounding area with a damp cloth until the surface is smooth.

5. If shrinkage occurs, re-apply the above mixture.

6. Once the repair is completely dry and graining or marbling is finished, apply clear lacquer over the area using the brush.

Cal-Flor Accessory Systems  
1000 Cal Oak Road, Oroville, CA 95965  
(530) 534-1426  
Item # FL49115CF  
Run #16067

For more tips on creating graining and marbling, visit:  
[www.easysurfacerepairs.com](http://www.easysurfacerepairs.com)



### USE **WHITE** PUTTY ONLY FOR THESE FORMULAS

putty only		1
2 A, 2 C 1 Black 6 White	3 taps from bowl into 2 lines putty	2
1 A, 8 C 10 White 1 Yellow	1 tap from bowl into 1 line putty	3
1 A, 5 C 6 White	2 taps from bowl into 2 lines putty	4
8 A, 8 C	6 taps from bowl into 2 lines putty	5
1 A, 1 C	Add drops to 2 lines putty	6
2 A, 2 C 12 White 1 Black	12 taps from bowl into 2 lines putty	7
1 C 10 White	Add drops to 1 line putty	8
3 A, 12 C 3 Yellow	6 taps from bowl into 2 lines putty	9
2 A, 6 C	8 taps from bowl into 2 lines putty	10
1 A, 5 C 4 White	Add drops to 4 lines putty	11
2 A, 4 C	Add drops to 3 lines putty	12
4 A, 4 C	Add drops to 2 lines putty	13
4 A, 4 C	Add drops to 1 line putty	14
3 A, 5 C 1 Black	Add drops to 2 lines putty	15
10 A, 20 C 1 Black	Add drops to 1 line putty	16
22 A, 2 C 1 Black	14 taps from bowl into 2 lines putty	17
4 A, 4 C 1 Red	Add drops to 1 line putty	18
10 C, 8 A 1 Red	Add drops to 1 line putty	19
5A, 5C 2 Red 1 Black	Add drops to 1 line putty	20
20A, 1 Blue 10 Red	Add drops to 1 line putty	21
3A, 3 Red 3C, 3 Yellow 2 Green 3 Black	Add drops to 1 line putty	22
2A, 10C 3 Yellow	Add drops to 1 line putty	23
2A, 10 C	Add drops to 1 line putty	24
5A, 14 White 2 Black 1 Blue 2 Green	4 taps from bowl into 2 lines putty	25
1 C, 1 Black 1 Green 5 White	Add drops to 1 line putty	26
1 Black	Add drop to 1 line putty	27
20 Black	Add drops to 1 line putty	28

### Tile Formulas For Hard Surfaces Like Tile, Stone, Concrete

### COLOR ADJUSTMENT TIPS

- Note: Tints are concentrated - use sparingly.
- The colors can be made lighter or darker by adding more or less putty or by adding the white tint to your mixture.
- To achieve very light colors, add a small amount of the putty/tint mixture to some fresh putty until the desired lightness is achieved.
- To slightly alter colors, add tint to some fresh putty first, then add that to your existing mixture.
- For a more realistic repair, match the background color (usually much lighter) first, then add foreground graining or marbling.