

Aqua Mix® SameDay™ Grout Sealer

1 Product Name

Aqua Mix® SameDay™ Grout Sealer

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
 custombuildingproducts.com

3 Product Description

A no-sheen, natural look, water-based, nonflammable, aerosol sealer with a 360 nozzle specially formulated for grout. This innovative spray is a quick and easy way to apply a grout sealer. SameDay Grout Sealer can be applied as soon as 2 hours after grouting, making sealing an efficient, economical process. The easy-to-spray nozzle places more sealer on the grout.

Key Features

- Easy aerosol application
- No-sheen natural look
- Safe, nonflammable formula

Suitable Tile Types

- Cementitious sanded and unsanded porous grout joints for ceramic and porcelain tile installations
- Effective for interior and exterior applications

Limitations to the Product

- Do not allow sealer to come in contact with any non-recommended surface
- Sealer will not prevent surface wear or etching from acids

4 Technical Data

Environmental Consideration

Complies with all Federal EPA and SCAQMD standards for VOC

5 Instructions

General Surface Prep

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Stripper & Cleaner or Aqua Mix® Heavy-Duty Tile & Grout Cleaner will clean the surface or strip wax and acrylic finishes. Protect surrounding surfaces. Test product in an inconspicuous area to ensure desirable results.

Exterior applications must meet moisture conditions - [read CUSTOM Technical Bulletin 49](#) for details.

Application of Product

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.



Read entire label before using. Protect all surrounding surfaces. SHAKE WELL before using. For new installations, sealer can be applied as soon as 2 hours after grouting. Grout joints must be clean, dry, and free of existing sealers or coatings. Invert can and point nozzle toward the grout, keeping nozzle 18"-24" (45 cm to 60 cm) from the surface. Press nozzle forward and spray along grout lines. NOTE: Be sure to completely wipe surface DRY within 5 minutes of each application using dry paper, cotton or microfiber towels. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. Be careful not to directly rub fresh grout if sealer is applied same day as grout. After 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 3 hours and repeat the test. Ready for surface traffic 2 hours after final coat. Keep area dry for 24 hours after application. May be reapplied as needed to grout joints that are clean and dry.

Drying Time

- Allow 30 minutes drying time between coats.
- Ready for surface traffic in 2 hours.
- Keep dry for 24 hours.
- Achieves a full cure in 24 hours.

Cleaning of equipment

Clean tools with mineral spirits after use.

Health Precautions

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Do not breathe vapor or spray. Contains octyl triethoxy silane. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If respiratory tract is irritated, remove to fresh air. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

6 Availability & Cost

Location	Item Code	Size	Package
USA	100557	15 Oz. (444 ml)	Aerosol
Canada	C100557	15 Oz. (444 ml)	Aerosol



CUSTOM®

Aqua Mix® SameDay™ Grout Sealer

7 Product Warranty

Custom® Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. CUSTOM's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with CUSTOM's printed instructions. CUSTOM makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

8 Product Maintenance

Do not use cleaners containing ammonia, acids or bleach. Use an appropriate TileLab® or Aqua Mix® neutral cleaner. Tile industry experts recommend periodic testing of sealed surfaces. Apply a few drops of water on the surface. If it soaks in, an additional application of sealer will be necessary to keep sealer at peak performance.

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

Expected Wear

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear

Handling & Storage

- Close container tightly after each use.
- Store in original container only.
- Store away from heat.
- Store and use between temperatures of 45 °F - 85 °F (7.2 °C - 29.4 °C).

Related Products

Aqua Mix® AquaShield™ Cleaner & Resealer

Aqua Mix® AquaKleen™

Aqua Mix® Concentrated Stone & Tile Cleaner



Aqua Mix® SameDay™ Grout Sealer

Coverage

Size	Min Coverage	Max Coverage
15 oz (444 mL) Can	300 ft ² (28 M ²)	500 ft ² (46 M ²)



CUSTOM®