



Installer Friendly Reliable Security Money Savings

PC LED Floodlights

This is the ideal entry level floodlight to provide you with a low maintenance solution that is perfect for any security application.



white



bronze



Powering Business Worldwide

PC LED Floods Outdoor Security Lighting

Feature	Benefit	Result	
Performance	Selectable CCT (3000K, 4000K, 5000K)	1 SKU covers all applications	
	Up to 108 Lm/W, 50K life hours at L70	Save over 80% over traditional incandescent floodlights	
	Frosted wrap around lens	Low glare provides visual comfort; No call backs	
	5 year warranty	Guaranteed performance	
Construction	Patented motion swing arm	Wall and eave mountability; No call backs	
	UV resistant plastic housing	No issues with rusting over time	



Ordering Information

Series	Voltage	Power (W)	Delivered Lumens (Lm)	Efficacy (Lm/W)	CCT	UPC	Pallet Quantity	Controls
FT18VCB	120V	13.1	1346	102.7	3000K, 4000K, 5000K	080083837090	288	None
FT18VCW	120V	13.1	1346	102.7	3000K, 4000K, 5000K	080083837151	288	None
FT18VCIB	120V	13.1	1346	102.7	3000K, 4000K, 5000K	080083837113	288	Integrated Photocell
FT18VCIW	120V	13.1	1346	102.7	3000K, 4000K, 5000K	080083837137	288	Integrated Photocell
MST18VCB	120V	13.1	1346	102.7	3000K, 4000K, 5000K	080083837236	120	Motion Sensor
MST18VCW	120V	13.1	1346	102.7	3000K, 4000K, 5000K	080083837250	120	Motion Sensor
FT28VCB	120V	20.3	2200	108.4	3000K, 4000K, 5000K	080083837175	288	None
FT28VCW	120V	20.3	2200	108.4	3000K, 4000K, 5000K	080083837212	288	None
FT28VCIB	120V	20.3	2200	108.4	3000K, 4000K, 5000K	080083840168	288	Integrated Photocell
FT28VCIW	120V	20.3	2200	108.4	3000K, 4000K, 5000K	080083837199	288	Integrated Photocell
MST28VCB	120V	20.3	2200	108.4	3000K, 4000K, 5000K	080083837274	120	Motion Sensor
MST28VCW	120V	20.3	2200	108.4	3000K, 4000K, 5000K	080083837298	120	Motion Sensor

Competitor Comparison

= Market Leading

Feature	PC Floods	Competitor A	Competitor B
Lumens	1346/2200	1600/2000/2500	1770
Lm/W	Up to 108	Up to 72	Up to 89
CCT	Selectable (3K,4K,5K)	5000K	4000K
Mounting	Wall + Eave	Wall + Eave	Wall + Eave
Installation	-	Easy-Mount Plate	-
Voltage	120V	120V	120V
Lens	Frosted	Frosted	Clear
Listings	cULus	ETL	cULus
Warranty	5	5	5
Family	Flood, D2D, Motion	Motion only	D2D only