


















Exterior Woodcare and Concrete

Brand Name	Restore 10X Advanced	Restore 4X Deck Coat	Restore 2X One Coat Solid Stain with NeverWet Technology	Restore 2X One Coat Solid Stain with Cool Touch Technology	Restore Outdoor Furniture	Restore Solid Acrylic Stain	Restore Deck Start Wood Primer
							
Dry to Touch	6 hours	2 hours	6 hours	2 hours	2 hours	1 hour	1 hour
Recoat	4 - 6 hours	4 - 6 hours	1 Coat Coverage	1 Coat Coverage	4 hours	2 hours	1 Coat Coverage
Surfaces	Wood decks and docks, broom swept concrete and more	Wood and composite decks and docks, broom swept concrete and more	Wood and composite decks and docks, broom swept concrete and more	Wood and composite decks and docks, broom swept concrete and more	Outdoor application on most exterior wood furniture and play sets	Wood decks, railings, fences, siding, trim, retaining walls & more	Outdoor application on wood decks, fences, siding, furniture & more
Do Not Use On	Smooth or floated concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Smooth or floated concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Smooth or floated concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Smooth or floated concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Composite decking, concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Smooth or floated concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Any surface that is not wood
Deck / Surface Condition	Old and Worn in need of major repair	Light worn and weathered in need of light repair	New and lightly worn decks	New and lightly worn decks	Light worn and weathered in need of light repair	New and lightly worn decks	
Application Tip	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application
Horizontal and Vertical Surfaces	Horizontal	Horizontal and Vertical	Horizontal and Vertical	Horizontal and Vertical	Horizontal and Vertical	Horizontal and Vertical	Horizontal and Vertical
Coverage Sq Ft	40 per gallon	80 per gallon	250 per gallon	250 per gallon	80 per gallon	350 per gallon	450 per gallon
Finishes	60 Tint Colors	60 Tint Colors	60 Tint Colors	2 Pre-Tinted Colors	15 Tint Colors	60 Tint Colors	Goes on milky white and dries clear
# of Coats	2	2	1	1	2	2	1
Interior/Exterior Apply with	Exterior 4" or 9" Restore Honeycomb Roller	Exterior Brush or 3/8" or 1/2" nap roller	Exterior 3/8" nap roller or a synthetic paint brush	Exterior 3/8" nap roller or a synthetic paint brush	Exterior 4", 3/8" or 1/2" nap roller or a synthetic bristle brush	Exterior Brush, roller or spray	Exterior 3/8" nap roller or a synthetic bristle brush
Painting Conditions	50 to 90°F during application and for 48 hrs after application	50 to 90°F during application and for 72 hrs after application	50 to 90°F during application and for 6 hrs after application	50 to 90°F during application and for 6 hrs after application	50 to 90°F during application and for 72 hrs after application	50 to 90°F during application and for 24 hrs after application	50 to 90°F during application and 2 hrs after application
Ready to use	48 hours	3 to 5 days	48 hours	48 hours	3 to 5 days	24 hours	2 hours
What makes it unique?	10X thicker than ordinary paint Fills cracks up to 3/4" deep Ultimate water repellency Algae & Mildew resistant	4X thicker than ordinary paint Conceals hairline cracks Superior Coverage Barefoot friendly	2X thicker than ordinary paint One Coat application Ultimate water repellency Algae & Mildew resistant	2X thicker than ordinary paint Reduces surface temp up to 15 degrees One Coat application Superior water repellency Algae & Mildew resistant	4X thicker than ordinary paint Conceals hairline cracks Low-VOC, low odor Water-based formula Extends life of wood furniture	Water based formula Low odor, ultra-low VOC Deep penetrating formula for lasting protection	Simplifies preparation No Sanding or Stripping Promotes Topcoat adhesion Works with any solid topcoat Exceptional Coverage
SKU count	3	2	2	2	2	1	2
Available Sizes	1-Gallon 4-Gallon	1-Gallon 5-Gallon	1-Gallon 5-Gallon	1-Gallon	1-Quart 1-Gallon	1-Gallon	1-Gallon 5-Gallon

Exterior Woodcare and Concrete

Brand Name	Restore Semi-Transparent Metallic Stain & Sealant	Restore Semi-Transparent Stain & Sealant Neverwet	Restore 12X Transparent	Restore 12X Clear Coat	Restore Vertical	Restore Extreme Concrete Liquid Armor Resurfacer	Also Available
							<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>Restore Deck Stripper</p>  <ul style="list-style-type: none"> -Strips wood stain for better topcoat adhesion -Works in 15 minutes -Brush-on, power wash off -Removes all wood stains and sealants -Covers 150 sq ft per gallon </div> <div style="width: 45%;"> <p>Restore Roller Covers</p>  <p>Restore 4" Roller Kit includes: 1 heavy duty tight-fit roller frame with pole receptacle and 1 grid screen</p> </div> </div>
Dry to Touch	2 hours	2 hours	2 hours	2 hours	2 hours	2 hours	
Recoat	1 Coat Coverage	1 Coat Coverage	1 Coat Coverage	1 Coat Coverage	3 - 6 hours	3 - 6 hours	
Surfaces	Wood decks, fences, siding, furniture & more	Wood decks, fences, siding, furniture & more	Wood decks, fences, siding, furniture & more	Wood decks, fences, siding, furniture & more	Wood siding, brick, cement block, concrete, drywall and shake siding	Use on broom/brushed concrete driveways, patios and more	
Do Not Use On	Composite decking, concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Composite decking, concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Composite decking, concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Composite decking, concrete, fiberglass, tile, metal surfaces and areas with vehicular traffic	Aluminium siding or plastic siding	Smooth or floated concrete, Asphalt	
Deck / Surface Condition	New and lightly worn decks	New and lightly worn decks	New and lightly worn decks	New and lightly worn decks			
Application Tip	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application	Allow new wood decks to weather at least 6 months prior to application			
Horizontal and Vertical Surfaces	Horizontal and Vertical	Horizontal and Vertical	Horizontal and Vertical	Horizontal and Vertical	Vertical	Horizontal	
Coverage Sq Ft	200 per gallon	200 per gallon	250 per gallon	250 per gallon	30 per gallon	100 per 4-gallon pail	
Finishes	2 Metallic Colors	60 Tint Colors	6 Tint Colors	Clear	40 Tint Colors	40 Tint Colors	
# of Coats	1	1	1	1	2	2	
Interior/Exterior Apply with	Exterior Short nap stain pad or a synthetic paint brush	Exterior Short nap stain pad or a synthetic paint brush	Exterior 3/8" nap roller or a synthetic paint brush	Exterior 3/8" nap roller or a synthetic paint brush	Exterior 4" or 9" Restore Honeycomb Roller	Exterior 18" Restore Honeycomb Roller	
Painting Conditions	50 to 90°F during application and for 2 hrs after application	50 to 90°F during application and 2 hrs after application	50 to 90°F during application and for 6 hrs after application	50 to 90°F during application and for 6 hrs after application	50 to 90°F during application and for 72 hrs after application	50 to 90°F during application and for 72 hrs after application	
Ready to use	48 hours	48 hours	48 hours	48 hours	72 hours	12 hours foot traffic & 7 days vehicle traffic	
What makes it unique?	Unique Metallic Finish One Coat application Stain & Sealant in one Superior water repellency Algae & Mildew resistant	One Coat application Stain & Sealant in one Superior water repellency Algae & Mildew resistant	12X thicker than ordinary sealers One Coat application Crystal Clear finish Low VOC, low odor Superior water repellency Algae & Mildew resistant	12X thicker than ordinary sealers One Coat application Crystal Clear finish Low VOC, low odor Superior water repellency Algae & Mildew resistant	10X thickwe than ordinary paint Fills hairline cracks Repairs and protects vertical surfaces Water-based, low odor Hides imperfections Moisture protection	Pigmented water-proofing sealer Fills hairline cracks Withstands extreme weather & heavy usage Water-based, low odor Resists hot tire pick up	<p>Restore Crack Filler</p>  <ul style="list-style-type: none"> -Fills cracks up to 3/8" -Durable, flexible and waterproof -Works on wood and concrete -Adheres to painted and unpainted wood, concrete and masonry -Covers up to 50 ft when
SKU count	2	1	1	1	2	1	
Available Sizes	1-Gallon	1-Gallon	1-Gallon	1-Gallon	1-Gallon 4-Gallon	4-Gallon	<p>Restore 18" x 3/8" Honeycomb Roller Cover</p>  <p>Restore 9" x 3/8" Honeycomb foam roller cover</p> 