

SAFETY DATA SHEET



Section I - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Latexite[®] 3.4 Gal. Acrylic Grade Sealer (Blacktop)

Manufacturer Name: Dalton Enterprises, Inc.

Item #: 31780

UPC #: 0 90932 31780 2

Address: 131 Willow Street Cheshire, CT 06410

Telephone Number: (203) 272-3221

24 Hour Emergency Number: (203) 272-3221

U.S. And Canada: (203) 272-3221

Trade Names and Synonyms: Acrylic Copolymer Emulsion **Recommended Use and Restrictions:** Blacktop Coatings / Sealant

Product Description: Consumer packaged (ready-to-use) Latex•ite[®] Acrylic Grade sealer is for asphalt surfaces. Proper application of ready-to-use emulsified product as applied presents no degree of hazard to the user. Outdoor use only.

Section II - HAZARDS IDENTIFICATION

Classification

Skin Corrosion/Irritation	Category 2
Serious Eye Damage, Eye Irritation	Category 2B

Label Elements



GHS Pictogram:

Signal Word: Warning

Hazard Statements: Causes skin irritation Causes eye irritation

Precautionary Statements – Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Dalton Enterprises, Inc.

Product: Latex-ite® Acrylic Grade

Phone: (203) 272-3221 SDS Date: 01/10/2019

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, Get medical advice/attention.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms, Call a POISON CENTER or doctor/physician.

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

No information available

Interactions with Other Chemicals

No information available.

Section III - COMPOSITION

CAS#	<u>Component</u>	% Composition
14808-60-7	Crystalline Silica*	5 – 10%
1333-86-4	Carbon Black (pigment)*	0 – 6%

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

Section IV - FIRST-AID MEASURES

Emergency and First Aid Procedures

General Advice: Present this safety data sheet to the physician in attendance. **Eye Contact:** Flush thoroughly with water. If irritation persists, see a physician.

Skin Contact: Clean exposed area thoroughly with soap and water. If irritation persists, see a physician.

Ingestion: If swallowed do NOT induce vomiting. Seek medical attention if symptoms develop.

Inhalation: Move to fresh air if symptoms develop. If irritation persists, see a physician.

Most Important Symptoms: Possibility of minor eye and skin irritation.

Indication of Immediate Medical Attention and Special Treatment Needed: Treat Symptomatically

Section V - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical, carbon dioxide, foam and water fog.

Unsuitable Extinguishing Media: N/A

Specific Hazards arising From the Chemical: Combustion may yield oxides of carbon, hydrogen sulfide

and sulfur oxides.

Special Protective Equipment and Precautions for Firefighters: Wear full protective clothing, including self-contained breathing apparatus (Positive Pressure/Pressure Demand), helmet, and face mask.

Section VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Avoid skin and eye contact, use proper protective equipment recommended in section 8.

Methods and Materials for Containment and Cleanup: Contain spill and dike with inert material (sand, sawdust, dirt, etc.). Place in closed container for proper disposal. Avoid runoff to waterways and sewers. Dispose of in accordance with local regulations.

Section VII - HANDLING AND STORAGE

Precautions for Safe Handling: Store in a dry area, avoid eye contact and wash thoroughly after handling **Conditions for Safe Storage, Including Incompatibilities:** Keep container closed and upright to prevent leakage. Store in a cool, dry, ventilated area. Avoid freezing. Keep container upright to prevent leakage.

Section VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TWA	OSHA PEL (TWA) (mg/m3)	NIOSH IDLH
	(mg/m ³)		
Carbon Black	3 mg/m ³	3.5 mg/m^3	1
Crystalline Silica	0.025 mg/m ³	(30)/(% SiO2 + 2) mg/m3 TWA, total	0.05 mg/m3 TWA (respirable
	TWA	dust	dust)
	(respirable dust)	(250)/(% SiO2 + 5) mppcf TWA,	
		respirable fraction	
		(10)/(% SiO2 + 2) mg/m3 TWA,	
		respirable fraction	

Engineering Controls: Ensure adequate ventilation

Individual Protection Measures

Eyes/Face: Safety goggles

Skin: Gloves

Respiratory: None required if good ventilation is maintained. This product is an emulsified, encapsulated mixture which greatly reduces the likelihood of exposure to hazardous particles.

Dalton Enterprises, Inc.

Product: Latex-ite® Acrylic Grade

Phone: (203) 272-3221 SDS Date: 01/10/2019

Hygienic controls: Wash thoroughly with soap and water before eating or drinking. Wash contaminated clothing.

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black liquid Upper Explosive Limit: N/A Physical State: Liquid Lower Explosive Limit: N/A

Odor: Mild Acrylic Vapor Pressure: Nearly equal to water Odor Threshold: N/A Vapor Density: Heavier than air

pH: 6.0 – 7.0

Melting Point: N/A

Solubility In Water: Miscible

Boiling Point: N/A **Partition Coefficient (n-octanol/water):** N/A

Flash Point: N/A

Evaporation Rate: Slower than ether

Auto Ignition Temperature: N/A

Decomposition Temperature: N/A

Flammability: N/A Max Voc: < 25g/L

Section X - STABILITY AND REACTIVITY

Reactivity: None known under normal conditions

Stability: Stable

Hazardous Reactions: None known under normal conditions **Conditions to avoid:** Keep from freezing and extreme heat

Incompatibility: Strong oxidizers

Hazardous Decomposition Products: Combustion may yield fumes, smoke, carbon monoxide and carbon

dioxide.

Section XI - TOXICOLOGICAL INFORMATION

Health Effects

Eye Contact: Minor irritation may result Skin Contact: Minor irritation may result Ingestion: Minor irritation may result Inhalation: Minor irritation may result

Toxicological Effects

Component	CAS # Acute oral toxicity LD50 Acute		Acute dermal toxicity LD50
Carbon Black	1333-86-4	> 8,000 mg/kg (rat)	no data available
Crystalline Silica	14808-60-7	>22,500 mg/kg (rat)	no data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization: Product not known to cause sensitization

Mutagenic Effects: None known

Carcinogenicity: Product not known to cause cancer

Component	CAS#	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
Carbon Black	1333-86-4	2B	Not Listed	-
Crystalline Silica	14808-60-7	Group 1	Known	-

NOTE: Crystalline silica in respirable form is carcinogenic to humans. The crystalline silica present is not respirable as this product is supplied.

NOTE: Carbon Black in respirable form is carcinogenic to humans. The Carbon Black present is not respirable as this product is supplied.

Reproductive Toxicity: No toxicity known STOT – Single Exposure: None Known STOT – Repeated Exposure: None Known Chronic Toxicity: No Known Effect Target Organ Effects: Eyes, Skin.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Numerical Measures of Toxicity

No data available

Section XII - ECOLOGICAL INFORMATION

Ecological Fate:No data availablePersistence/Degradability:No data availableBioaccumulation Potential:No data availableMobility in Soil:No data availableOther Adverse Effects:No data available

Analysis for ecological effects has not been conducted.

Section XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with Local, State, and Federal regulations.

Section XIV - TRANSPORT INFORMATION

DOT – U.S. Department of Transportation

Proper Shipping Name: Not regulated TDG - Canada - Transport of Dangerous Goods Proper Shipping Name: Not Restricted IATA – International Air Transport Association Proper Shipping Name: Not regulated IMDG – International Maritime Dangerous Goods

Proper Shipping Name: Not regulated

Section XV - REGULATORY INFORMATION

International Inventories

TSCA: Complies

DSL/NDSL: Complies

US Federal Regulations

SARA 313: This product contains no chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372)

SARA Hazard Category (311/312): Non Hazardous

CWA (Clean Water Act): This product contains no chemicals regulated by the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA: This product contains no substances regulated by the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

Component Name	CAS	State Right to Know		
		MA	NJ	PA
Carbon Black	1333-86-4	yes	yes	yes
Crystalline Silica	14808-60-7	yes	yes	yes

California Proposition 65:

WARNING: This product can expose you to chemicals including carbon black and crystalline silica, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NOTE: Carbon Black in respirable form is carcinogenic to humans. The Carbon Black present is not respirable as this product is supplied.

NOTE: Crystalline silica in respirable form is carcinogenic to humans. The crystalline silica present is not respirable as this product is supplied.

International Regulations

WHMIS: Non Hazardous

Section XVI - OTHER INFORMATION

Other Precautions:

Do not take internally.

Keep away from children.

For external use only.

Store in a cool, dry place.

Keep away from sources of ignition.

Do not apply during or before rain to avoid runoff.

Do not apply if pavement is below 55 degrees F.

NFPA Rating: Health 1; Fire 0: Reactivity 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Revision Date: 01/10/2019

Disclaimer/Statement of Liability:

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AND ARE BASED UPON EXPERIENCE, TESTS, LITERATURE REFERENCES, AND/OR CALCULATIONS. THE MANUFACTURER MAKES NO GUARANTEE, EXPRESSED OR IMPLIED, AS TO THE AFFECT OF USE, OR THE SAFETY AND TOXICITY OF THE PRODUCT. THE INFORMATION CONTAINED IN THIS SHEET CANNOT BE TAKEN AS THE SUM TOTAL OF ALL PROTECTIVE MEASURES TO BE TAKEN.