

## **WARRANTY AND DISCLAIMER**

### **WARRANTY**

Deterioration of topical treatments can occur due to atmospheric conditions, cleaning of the surface and many other conditions beyond our control. No additional coatings should be applied to a treated surface as it can change the flame-spreading ratings. Fire retardants shall possess the degree of permanency and shall be maintained so as to retain the effectiveness of the treatment under the service conditions encountered in actual use. Periodic testing and inspection should be performed by a trained individual to insure flame-retardancy. Shelf life for latex coatings is 1 year if pail is unopened and stored from freeze protection and extreme heat. If storing for long periods of time, it would be best to shake or turn pail to allow periodic mixing of the product. Make sure products are mixed well prior to using.

For soft-goods, Firetect will not be responsible for any color change, shrinkage, wrinkling, aesthetic change and stiffness of fabric or sun fade on any fabric or material processed with its flame retardants, as dyes and fabric fibers can vary. Firetect is not responsible for any electrical shortages, power failures, electrical or aesthetic damage to equipment and/or obstacles near work area. They will need to be covered, masked protected and/or moved. Customers must provide working clearance. Nor does it guarantee against any fabric reaction due to exposure to condensation or atmospheric conditions in the air. This information is standard to the flame retarding industry and in accordance to NFPA Compliance. In addition, because our products are water based, when the flame retardant comes in contact with metal surfaces, rusting and/or tarnishing can occur. Never allow flame retarded fabric to come in contact with any liquids. Dry cleaning of fabric is recommended, but flame retardant may be removed by washing or dry cleaning.

### **DISCLAIMER**

Use only as directed. Sellers and Manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, user must determine the suitability of the product for its intended use. The user assumes all risk and liability whatsoever in connection therewith. Any statement or recommendation not contained herein shall have no force or effect unless contained in an agreement signed by officers of seller and manufacturer. Deterioration of coatings applied to interior finishes can occur due to ambient conditions and repeated cleaning of the surface or painting over applied coatings. Fire Retardants shall possess the desired degree of permanency and shall be maintained so as to retain the effectiveness of the treatment under the service conditions encountered in actual use. Periodic testing and inspection is recommended.