



STOPS RUST® ADVANCED SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Stops Rust® Advanced Sprays are designed to provide a durable protective coating with excellent rust prevention, and excellent resistance to abrasion, fading, chipping, and dulling. Stops Rust Advanced provides 30% greater corrosion resistance and color retention when compared to original matching Stops Rust colors. These sprays apply easily, provide excellent coverage and dry fast to a tough attractive finish. Rust-Oleum Stops Rust Advanced Sprays are ideal for ferrous, non-ferrous metal and wood surfaces. It features a high-output comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and an any-angle tip which allows you to spray at any angle. Not for use on galvanized metal.

PRODUCTS

SKU	DESCRIPTION (12 oz. Aerosol)
338882	Gloss Antique White
338884	Gloss Almond
338885	Gloss Harbor Blue
338919	Gloss Sunrise Red
338920	Gloss Regal Red
338921	Gloss Cherry
338922	Gloss Sunburst Yellow
338923	Gloss Sail Blue
338924	Gloss Smoke Gray
338927	Gloss Black
338928	Gloss White
338929	Gloss Orange
338931	Gloss Poppy Pink
338932	Gloss Willow Green
338934	Gloss Deep Mint
345391	Gloss Hunter Green
338926	Gloss Leather Brown
345392	Gloss Dark Walnut
345389	Gloss Charcoal Gray
338918	Gloss Light Turquoise
338935	Gloss Cobalt
338944	Semi-Gloss Black
338945	Semi-Gloss White
338937	Satin White
338938	Satin Black
338939	Satin Dark Brown
338940	Satin Classic Navy
338941	Satin Coastal Gray
338942	Satin Hunter Green
338943	Satin Fire Red
345398	Satin Shell White

PRODUCTS (cont.)

SKU	DESCRIPTION (12 oz. Aerosol)
338946	Flat White
338947	Flat Brown
338948	Flat Black
SKU	DESCRIPTION (15oz. Aerosol)
352534	Gloss Black
352535	Gloss White
352536	Flat Black
352537	Flat White
352538	Semi-Gloss Black
352539	Semi-Gloss White

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRIMING

Use of a Stops Rust® Primer provides added corrosion protection, superior adhesion and hiding and is especially recommended for bare wood and metal.



STOPS RUST® ADVANCED SPRAYS

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°-90°F (10°-32°C) and humidity is below 70% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 18-24" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. It is recommended to apply a light first coat, target 50% coverage. Apply 2 or more light coats a few minutes apart.

PRODUCT APPLICATION (cont.)

DRY AND RECOAT TIMES

Based on 70°F (21°C) 50% relative humidity. Allow more time at cooler temperatures. Dries tack-free in 2-4 hours, to handle in 5-9 hours, and is fully dry in 24 hours. Apply a second coat within 1 hour or after 48 hours.

CLEAN UP

Wipe off tip before storing. Clean up wet paint with Xylene or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.

 	TECHNICAL DATA	SRT-45
STOPS RUST® ADVANCED SPRAYS		

PHYSICAL PROPERTIES

		STOPS RUST ADVANCED SPRAYS
Resin Type		Oil modified Alkyd
Pigment Type		Varies depending on color
Solvents		Acetone, N-Butyl Acetate, Aromatic Hydrocarbons
MIR		Flat - 0.80 max Gloss, Satin, Semi-Gloss - 0.95 max
Fill Weight		12 and 15 oz.
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils
Practical Coverage at Recommended DFT (assume 15% material loss)		6-10 sq.ft./12oz. can 7.5-12.5 sq.ft./15oz. can
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	2-4 hours
	Handle	5-9 hours
	Recoat	Before 1 hour and after 48 hours
Shelf Life		5 years
Flash Point		156°F (69°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.