SAFETY DATA SHEET

Issuing Date 20-Dec-2016 Revision Date 12-Dec-2016 Revision Number 2

(UL)

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name 2Ah Rechargeable Lithium Ion Battery Pack EP20 40V 80Wh

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Frictionless World

Supplier Address 1100 West 120th Avenue

Suite 600 Westminster

CO 80234 US

Supplier Phone Number Phone:720-287-5182

Supplier Email kabegg@frictionlessworld.com

Emergency telephone number

Company Emergency Phone

Number

720-287-5182

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1



Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Causes severe skin burns and eye damage

May cause cancer

Causes damage to organs through prolonged or repeated exposure



. This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance No information available

Physical state Solid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up



Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

23 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed May be harmful in contact with skin Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical name	CAS No	Weight-%	Trade Secret
Cobalt lithium manganese nickel oxide	182442-95-1	15 - 40	*
Graphite	7782-42-5	10 - 30	*
Ci 77400	7440-50-8	10 - 30	*
Iron	7439-89-6	10 - 30	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	7 - 13	*
Aluminum	7429-90-5	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance. First aid is upon rupture of sealed battery.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present

and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Seek immediate medical attention/advice.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention

immediately if symptoms occur.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give

anything by mouth to an unconscious person. Call a physician or poison control center



immediately.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Burning sensation. Coughing and/ or wheezing.

Effects

Notes to Physician

Indication of any immediate medical attention and special treatment needed

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood

pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



Page 4/14

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe

areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Should not be released into the

environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash

before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure GuidelinesThe following ingredients are the only ingredients of the product above the cut-off level (or

level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other

recommended limit. At this time, the other relevant constituents have no known exposure

limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Cobalt lithium manganese	TWA: 0.02 mg/m ³ Co TWA: 0.02	(vacated) Ceiling: 5 mg/m ³	IDLH: 500 mg/m³ Mn



niakal avida	ma/m3 Mn rooniroble norticulate metter	Cailing, F. ma/m3 Ma	IDLU: 10 ma/m3 Ni
nickel oxide	mg/m³ Mn respirable particulate matter	Ceiling: 5 mg/m³ Mn	IDLH: 10 mg/m³ Ni
182442-95-1	TWA: 0.1 mg/m³ Mn inhalable		TWA: 1 mg/m³ Mn
	particulate matter		TWA: 0.015 mg/m³ except Nickel
			carbonyl Ni
			STEL: 3 mg/m³ Mn
Graphite	TWA: 2 mg/m³ respirable particulate	TWA: 15 mg/m³ total dust synthetic	IDLH: 1250 mg/m ³
7782-42-5	matter all forms except graphite fibers	TWA: 5 mg/m³ respirable fraction	TWA: 2.5 mg/m³ respirable dust
		synthetic	
		(vacated) TWA: 2.5 mg/m³ respirable	
		dust natural	
		(vacated) TWA: 10 mg/m³ total dust	
		synthetic	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction synthetic	
		TWA: 15 mppcf natural	
Ci 77400	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³	TWA: 0.1 mg/m ³ fume	IDLH: 100 mg/m3 dust, fume and mist
7440-50-8	Cu dust and mist	TWA: 1 mg/m ³ dust and mist	TWA: 1 mg/m ³ dust and mist
		(vacated) TWA: 0.1 mg/m ³ Cu dust,	TWA: 0.1 mg/m ³ fume
		fume, mist	
Phosphate(1-), hexafluoro-,	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F	
lithium	g .	TWA: 2.5 mg/m³ dust	
21324-40-3		(vacated) TWA: 2.5 mg/m ³	
Aluminum	TWA: 1 mg/m³ respirable particulate	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
7429-90-5	matter	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable dust
		(vacated) TWA: 15 mg/m³ total dust	5g
		(vacated) TWA: 5 mg/m³ respirable	
		fraction (vacated) TWA: 5 mg/m³ Al	
		Aluminum	
		Auminum	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

Wash hands before breaks and immediately after handling the product. Take off

contaminated clothing and wash before reuse.



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Solid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor ThresholdNo information available

PropertyValuesRemarksMethodpHNo data availableNone known

Melting / freezing point

No data available

None known

None known

Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
No data available
No data available

None known Vapor pressure Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Insoluble in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known None known

Kinematic viscosityNo data availableDynamic viscosityNo data availableExplosive propertiesNo data availableOxidizing propertiesNo data available

Other Information

Softening Point

VOC Content (%)

Particle Size

No data available

No data available

No data available

Particle Size Distribution



10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information



Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Iron	= 984 mg/kg (Rat)	-	-
7439-89-6			

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Cobalt lithium manganese	A3	Group 2B	Known	X
nickel oxide		Group 1		
182442-95-1		·		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse

liver effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System

(CNS). Central Vascular System (CVS). Kidney. Liver. Lungs. Nasal cavities. Digestive

System.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)



2,156.00 mg/kg ATEmix (dermal) 2,100.00 mg/kg (ATE)

12. ECOLOGICAL INFORMATION

EcotoxicityVery toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to	Daphnia Magna (Water
		-	Microorganisms	Flea)
Ci 77400	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 - 0.0156		48h EC50: = 0.03 mg/L
7440-50-8	mg/L (Pseudokirchneriella	mg/L (Pimephales promelas)		
	subcapitata) 72h EC50:	96h LC50: = 1.25 mg/L		
	0.0426 - 0.0535 mg/L	(Lepomis macrochirus) 96h		
	(Pseudokirchneriella	LC50: = 0.052 mg/L		
	subcapitata)	(Oncorhynchus mykiss) 96h		
		LC50: = 0.2 mg/L		
		(Pimephales promelas) 96h		
		LC50: < 0.3 mg/L		
		(Pimephales promelas) 96h		
		LC50: = 0.112 mg/L		
		(Poecilia reticulata) 96h		
		LC50: = 0.3 mg/L (Cyprinus		
		carpio) 96h LC50: = 0.8		
		mg/L (Cyprinus carpio)		
Iron		96h LC50: = 13.6 mg/L		
7439-89-6		(Morone saxatilis)		

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.



Page 10/14

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

> CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Cobalt lithium manganese nickel oxide	Toxic
182442-95-1	
Ci 77400	Toxic
7440-50-8	
Aluminum	Ignitable powder
7429-90-5	- '

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

DOT NOT REGULATED **Proper Shipping Name** NON REGULATED

Hazard Class N/A **Emergency Response Guide**

Number

147

TDG Not regulated

MEX Not regulated

ICAO Not regulated

Not regulated NON REGULATED **Proper Shipping Name**



Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A F-A, S-I

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Not determined DSL Not determined

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Cobalt lithium manganese nickel oxide - 182442-95-1	182442-95-1	15 - 40	1.0 0.1
Ci 77400 - 7440-50-8	7440-50-8	10 - 30	1.0
Aluminum - 7429-90-5	7429-90-5	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese		X		
nickel oxide				
182442-95-1				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ci 77400			RQ 5000 lb final RQ
7440-50-8			RQ 2270 kg final RQ

US State Regulations



California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Cobalt lithium manganese nickel oxide - 182442-95-1	Carcinogen

U.S. State Right-to-Know Regulations

.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Cobalt lithium manganese nickel oxide	X		X	X	X
182442-95-1					
Graphite	X	X	X		
7782-42-5					
Ci 77400	X	X	X	X	X
7440-50-8					
Phosphate(1-), hexafluoro-, lithium	X				
21324-40-3					
Aluminum	X	X	X	X	
7429-90-5					

International Regulations

Mexico

National occupational exposure limits

Chemical name	Carcinogen Status	Exposure Limits
Cobalt lithium manganese nickel oxide		Mexico: TWA 0.2 mg/m ³
Graphite		Mexico: TWA= 2 mg/m ³
Ci 77400		Mexico: TWA 0.2 mg/m³ Mexico: TWA 1 mg/m³ Mexico: STEL 2 mg/m³
Aluminum		Mexico: TWA= 10 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and Chemical Hazards HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501 20-Dec-2016

Issuing Date20-Dec-2016Revision Date12-Dec-2016

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination



with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

