



# NOBLE CLASSIC PLUS


## NOBLE CLASSIC PLUS XL

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	8" x 48" / 196.85mm x 1212.85mm (Plus) 9.5" x 60" / 234.95mm x 1517.65mm (Plus XL)	
Overall Thickness*	0.24" / 6.0mm	
Wear Layer	20 mil / 0.5mm, featuring <b>Tuff Shield</b> finish (Plus & Plus XL)	
Edge	Micro Beveled	
Standard Colors	8 standard planks (Plus) / 4 standard planks (Plus XL)	
Installation Method	Unipush Click	
Backing	1mm IXPE backing	
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial	
Recycled Content	This product contains no recycled content. 100% recyclable post-use	
Packaging	PLANK (Plus) 20.56 ft <sup>2</sup> (1.91 m <sup>2</sup> ) per carton 8 pieces per carton 44 cartons per pallet 20 pallets per 20' container	PLANK (Plus XL) 23.03 ft <sup>2</sup> (2.14 m <sup>2</sup> ) per carton 6 pieces per carton 56 cartons per pallet 14 pallets per 20' container
Weight Per Carton	42.66 lbs / 19.35 kg	47.67 lbs / 21.62 kg



Alaska Oak-NCR 9708

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




London Oak NCR 9701 (EIR)



York Oak NCR 9703 (EIR)



Oslo Oak NCR-9705 (EIR)



Toronto Oak NCR 9707 (EIR)



Driftwood NCR 9709 XL (EIR)



Timberlake NCR 9711 XL (EIR)




Berlin Oak NCR 9702 (EIR)



Paris Oak NCR 9704 (EIR)



California Oak NCR 9706 (EIR)



Alaska Oak NCR 9708 (EIR)



Berkshire NCR 9710 XL (EIR)



Torres NCR 9712 XL (EIR)

\*All measurements are nominal.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.