



Last Rev Date: 03/11/2015

Physical Properties

| | | |
|---|--|--|
| Appearance Black mastic | Flash Point 120° F | Solids By Weight 78% |
| Base Refined asphalt | Freezability Does not freeze | Specific Gravity @ 77° F (25°C) 1.12 |
| Color Black | Maximum VOC 250 g/l | Weight Per Gallon 9.1-9.5 lbs |
| Consistency @ 77° F Soft, easily trowelable paste | | |

Approvals and Certifications

Meets or exceeds ASTM Specification D-4586, Type I and 100% wet surface adhesion per ASTM D-3409
MIAMI-DADE COUNTY PRODUCT CONTROL APPROVED - HE208R is in compliance TAS 121 with Miami-Dade Cty
NOA #13-1119.05

Description

HE208R - HENRY 208R RUBBERIZED WET PATCH® ROOF LEAK REPAIR is a premium, rubberized roof sealant. Especially easy to spread in cold temperatures.

- Seals leaks on wet or dry surfaces
- Rubberized for strength and flexibility
- Works even under water or in driving rain
- Adheres and remains intact from 5°F to 120°F

Usage

Repairs holes, cracks and splits on:

- Composition roofs
- Mineral surface cap sheets
- Asphalt coated roofs
- SBS modified rubber roofs
- Metal and masonry roofs

Coverage

12 1/2 sq.ft. per gallon applied 1/8" thick.

Cartridge - 39 lineal feet of 3/8" bead per 29 fl. oz. (857 ml) cartridge

Surface Preparation

CLEAN: Clean dirt and loose material from surface. Remove embedded gravel and cut away old roof cement to ensure bond. Remove rust and scale with wire brush.

Application

For Cartridge: Cut nozzle at angle, puncture inner seal, and apply with caulking gun.

Work into hole 1/8" to 1/4" thick with a trowel or putty knife. Press firmly and spread at least 2" beyond, feathering edges. If hole is over 1/4" wide or 2" long, reinforce with **HENRY 181** or **183 Roof Repair Fabric** between two layers of cement. For vertical surfaces in hot weather, use **HENRY 204® Plastic Roof Cement** or **HENRY 505 FlashMaster™ Flashing Cement**. **Henry Roof Repair Fabric** required for 10 year warranty.

Precautions

DO NOT THIN. Do not heat container or store at temperatures greater than 110°F (43°C). When transporting, make sure the pail is secured and the lid is tight to prevent spills. **CLOSE AIR INTAKES ON ROOF UNTIL SOLVENTS DISSIPATE!** May not yield satisfactory results over some APP torch down membranes. Contact Henry and membrane manufacturer before use. Not recommended for use over gravel, rubber or PVC sheet roofing or wood shingles. To extend repair life, coat with a Henry Roof Coating after 30 days.

NOTE: Asphalt-based coatings form a water soluble residue as they weather. In areas without regular rainfall, the roof should be hosed off occasionally to prevent build up and discoloration (removable with soap and water). Areas that pond water may accumulate more asphalt residue.

Cleanup

Clean tools with **Henry Scrubbers™ Hand & Tool Cleaning Towels** or kerosene, paint thinner or mineral spirits. Clean hands with waterless hand cleaner.

Caution

WARNING! Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

Prevention: Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep containers tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Avoid breathing vapors, mists and sprays. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection.

Response: In case of fire, use alcohol foam, carbon dioxide (CO₂) or dry chemical to extinguish. **IF ON SKIN:** Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs; Get medical advice or attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage: Store locked up. Store in a well-ventilated place. Keep cool. **Disposal:** Dispose of contents/containers in accordance with local/regional/national/international regulations.

See Safety Data Sheet for further details regarding the safe use of this product.

KEEP OUT OF REACH OF CHILDREN

FOR EXTERIOR USE ONLY

WARNING: This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Product Sizes

10.1 OZ CART (0 lb)
GALLON (10.9 lb)

29 OZ CARTRIDGE (0.86 lb)
3.5 GALLON (35 lb)

10.1 / 10.3/ 11 OZ (0.86 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will provide at no charge replacement product if the applicator proves, to our satisfaction, this product was defective within 10 years from purchase date of the product. We will consider this product defective if it does not perform its intended application provided it has been applied in accordance with our written instructions and used with Henry Repair Fabric. Proof of purchase must be provided for this warranty to be effective. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.** This limited warranty is in addition to and supplemented by the product warranty located on our website at: www.henry.com/warranty which also applies to this product.