



**RENOVATOR™
FENCE STAIN**

DESCRIPTION AND USES

Rust-Oleum® Renovator™ Fence Stain is a ready-to-use water-based formula designed to add color to vertical wood surfaces such as fencing, arbors, trellises and planter boxes. Renovator Fence Stain transforms your fence in minutes with vivid color that will last all season long.

Renovator Fence Stain is suitable for use on uncoated, weathered wood fences. **FOR EXTERIOR USE ONLY.**

PRODUCTS

SKU	Description
321637	Redwood (56 Fluid Ounces)
321639	Saddle Brown (56 Fluid Ounces)

PRODUCT APPLICATION

SURFACE PREPARATION

Protect any surfaces or shrubbery from overspray using drop cloths where applicable. If overspray does occur, clean using a mild cleaning agent such as Krud Kutter® Original cleaner and water.

For uncoated fences, clean the surface using a deck brush to remove any loose dirt and debris. For heavily soiled fences, use of a deck or fence wash product is recommended to remove mildew, mold, algae, fungus and moss. Let the surface dry.

For previously coated fences, all coatings should be removed prior to application.

Allow the fence to dry completely before applying Renovator Fence Stain. Dry times will vary based on wood species, fence location and weather.

PRODUCT APPLICATION (cont)

APPLICATION

For best results, use when outside temperatures are between 50°F (10°C) and 90°F (32°C) and when 24 hours of precipitation free weather is expected.

Attach a garden hose to the back of the hose end sprayer with the valve on the sprayer in the "OFF" position. Turn on the water. Aiming away from the fence, move the valve to the "RINSE" position to confirm water is flowing.

Stand about 2-3 feet away from the fence, rotate the valve to the far right position and begin coating the fence. Product will flow quickly. For best results, apply by moving your spraying hand vertically up and down in front of the fence panels as you walk along the length of the fence.

COVERAGE

One coat will cover up to 700 square feet per bottle. If a darker shade is desired, wait until the first coat is dry before applying additional product, usually about 1 hour.

DRY TIMES

Dry times are based on 70°F and 50% relative humidity. The product to dry to touch in 15 minutes, to handle in 1 hour and can be recoated in 2 hours. The coating will be fully cured in 24 hours.

CLEAN UP

Use mild soap and water.

STORAGE

KEEP FROM FREEZING. CLOSE CONTAINER AFTER EACH USE TO PRESERVE THE PRODUCT.

KEEP OUT OF REACH OF CHILDREN



TECHNICAL DATA

RENOVATOR™ FENCE STAIN

PHYSICAL PROPERTIES

		RENOVATOR FENCE STAIN
Composition		Acrylic
Pigment Type		Inorganic Oxides
Solvents		Water
Weight	Per Gallon	9.4-9.5 lbs.
	Per Liter	21.13-1.14 kg
Solids	By Weight	45.0-46.0%
	By Volume	37.3-37.8%
Volatile Organic Compounds		<100 g/l (0.83 lbs./gal.)
Practical Coverage		Approximately 700 sq.ft./bottle. One coat is required.
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	15 minutes
	Recoat	1 hour
	Full Cure	24 hours
Shelf Life		3 years
Flash Point		>200°F (93°C)
Storage		KEEP FROM FREEZING
Safety Information		For additional information, see the SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.